

SpecSeal® Smoke ‘N’ Sound Smoke and Acoustical Sealant

by Specified Technologies Inc.

HPD UNIQUE IDENTIFIER: 127250360320
HPD UNIQUE PRODUCT ID: Not provided.
CLASSIFICATION: 07 92 19 Acoustical Joint Sealants

PRODUCT DESCRIPTION: SpecSeal® Smoke ‘N’ Sound Sealant is a high quality acrylic latex sealant designed for sealing through-penetrations (such as pipes, conduits, cabling, busways, openings), membrane penetrations (such as p-traps and outlet boxes) in smoke rated walls. SpecSeal® Smoke ‘N’ Sound may also be used in linear applications such as wall-to-wall and head-of- wall joints where joints are designed to be either static or minimally dynamic. SpecSeal® Smoke ‘N’ Sound Sealant is available in a single grade that has excellent caulking properties as well as high build properties on vertical or overhead surfaces. This single grade may be caulked (standard cartridge or bulk loaded), knifed or troweled. In addition, SpecSeal® Smoke ‘N’ Sound contains no PCB’s nor asbestos. SpecSeal® Smoke ‘N’ Sound Sealant is storage stable (when stored according to the manufacturer’s recommendations), is asbestos free and will not separate nor excessively shrink when dried. Smoke ‘N’ Sound will adhere to all common construction and penetrant materials and contains no solvents that might adversely affect cable jackets. Applications: SMOKE CONTROL: Where stopping the passage of smoke is necessary such as in smoke barrier walls. NOISE CONTROL: Where reducing the transmission of sound through wall openings is necessary to help ensure occupant privacy and peaceful environment. INFECTIOUS/DUST CONTROL: Where reducing the transmission of dust and other airborne particulates through wall openings is necessary. Performance: SpecSeal® Smoke ‘N’ Sound Sealant has superb color stability and resistance to ultraviolet rays, ozone, and airborne contaminants. It is also mildew resistant and meets Class A finish requirements for Flame Spread and Smoke Development when tested in accordance with ASTM E84. SpecSeal® Smoke ‘N’ Sound Sealant provides less than one cfm air leakage when tested in accordance with UL1479 and UL2079 and is also acoustically tested and Certified, demonstrating excellent sound attenuation properties.

SCREENING DATE: 2026-04-14
PUBLISHED DATE: 2026-04-14
EXPIRY DATE: 2029-04-14
PREPARER: Self-Prepared

Health Product Declaration v3.0

created via: HPDC Online Builder

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Residuals/Impurities Evaluation	For all contents above the threshold, the manufacturer has:
→ Basic Method	→ Completed	
Threshold Disclosed Per	Explanation(s) provided :	Characterized
→ Product	Yes	Provided weight and role.
Threshold Level		Screened
→ 1,000 ppm		Provided screening results using HPDC-approved methods.
		Identified
		Provided name and CAS RN or other identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SPECSEAL® SMOKE ‘N’ SOUND SMOKE AND ACOUSTICAL SEALANT [LIMESTONE, CALCIUM CARBONATE BM-3dg
UNDISCLOSED NoGS WATER BM-4 ALCOHOLS, C8-22, ETHOXYLATED LT-UNK | SKI | EYE PROPYLENE GLYCOL BM-2 | END
| MAM TITANIUM DIOXIDE BM-1 | CAN | END | MAM SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC LT-P1 | END | MAM ETHYLHYDROXYETHYLCELLULOSE LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 2
Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... BM-1, LT-P1
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

None.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 20 Regulatory (g/l): 250
Does the product contain exempt VOCs: No
Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

COMPLIANCE See Section 3 for additional listings.
VOC emissions: UL/GreenGuard Gold Certified
VOC content: SCAQMD Rule 1168 Adhesive and Sealant Applications - Adhesives for Wood Flooring, Rubber Floor, Ceramic Tile, Multipurpose Construction, Structural Glazing and Contact, as amended 1/7/05
VOC content (amended): SCAQMD Rule 1168 Adhesive and Sealant Applications - Adhesives for Wood Flooring, Rubber Floor, Ceramic Tile, Multipurpose Construction, Structural Glazing and Contact, as amended 11/4/2022

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 3.0, available on the HPDC website at: www.hpd-collaborative.org/hpd-3-0-standard

SPECSEAL® SMOKE ‘N’ SOUND SMOKE AND ACOUSTICAL SEALANT

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: Crystalline Silica is a residual in this product.

OTHER PRODUCT NOTES: Crystalline Silica is a residual in this product.

LIMESTONE, CALCIUM CARBONATEID: 1317-65-3

HAZARD DATA SOURCE:Pharos Chemical and Materials LibraryHAZARD SCREENING DATE:2026-04-14 8:18:58

%:50.0000 - 65.0000GreenScreen:BM-3dgRC:NoneNANO:NoSUBSTANCE ROLE:Filler

HAZARD TYPELIST NAME AND SOURCEWARNINGS

None foundNo warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGSLIST NAME AND SOURCENOTIFICATION

None foundNo listings found on Additional Hazard Lists

SUBSTANCE NOTES: This material is used as a filler in the product.

UNDISCLOSEDID: Undisclosed

HAZARD DATA SOURCE:Pharos Chemical and Materials LibraryHAZARD SCREENING DATE:2026-04-14 8:18:59

%:35.0000 - 45.0000GreenScreen:NoGSRC:NoneNANO:NoSUBSTANCE ROLE:Binder

HAZARD TYPELIST NAME AND SOURCEWARNINGS

None foundNo warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGSLIST NAME AND SOURCENOTIFICATION

None foundNo listings found on Additional Hazard Lists

SUBSTANCE NOTES: This is the binder used in this product.

WATERID: 7732-18-5

SpecSeal Smoke N Sound Smoke and Acoustical Sealant

HPD v3.0 created via HPDC Builder Page 3 of 10

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:18:59	
%: 5.0000 - 8.0000	GreenScreen: BM-4	RC: None	NANO: No	SUBSTANCE ROLE: Carrier
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
None found			No warnings found on HPD Priority Hazard Lists	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
EXEMPT	European Union / European Commission (EU EC)		EU - REACH Exemptions Exempted from REACH Annex IV listing due to intrinsic safety	
SUBSTANCE NOTES: This material is a carrier in the product.				

ALCOHOLS, C8-22, ETHOXYLATED

ID: 69013-19-0

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2026-04-14 8:19:00		
%: 0.5000 - 1.5000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Surfactant
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
SKI	GHS - Australia		H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]	
EYE	GHS - Australia		H318 - Causes serious eye damage [Serious eye damage/eye irritation - Category 1]	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	
SUBSTANCE NOTES: This material is a surfactant in the product.				

PROPYLENE GLYCOL

ID: 57-55-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:19:00	
%: 0.5000 - 1.5000	GreenScreen: BM-2	RC: None	NANO: No	SUBSTANCE ROLE: Anti-freeze
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
END	TEDX - Potential Endocrine Disruptors		Potential Endocrine Disruptor	
MAM	GHS - Japan		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]	
MAM	GHS - Japan		H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]	

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List
		Antimicrobials
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List
		Some Solvents

SUBSTANCE NOTES: This is an antifreeze agent in the product.

TITANIUM DIOXIDE

ID: 13463-67-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:18:58	
%: 0.5000 - 1.5000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Pigment
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen		
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route		
CAN	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources		
CAN	MAK	Carcinogen Group 3A - Evidence of carcinogenic effects but not sufficient to establish MAK/BAT value		
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor		
CAN	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels		
CAN	IARC	Group 2b - Possibly carcinogenic to humans		
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]		
CAN	GHS - Japan	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
POSITIVE LIST	US Environmental Protection Agency (US EPA)	US EPA - DfE Safer Chemicals Ingredients list (SCIL)
		Colorants - Green Circle (Verified Low Concern)
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2025
		Cosmetics and Personal Care Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v5.0 Product Standard Restricted Substances - Effective March 16, 2026
		Cosmetics & Personal Care Products
SUBSTANCE NOTES: This is a pigment in the product.		

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC

ID: 64742-88-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:18:59	
%: 0.2500 - 1.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Diluent
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor		
MAM	EU - GHS (H-Statements) Annex 6 Table 3-1	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]		
MAM	EU - GHS (H-Statements) Annex 6 Table 3-1	H304 - May be fatal if swallowed and enters airways [Aspiration hazard - Category 1]		
MAM	GHS - Australia	H304 - May be fatal if swallowed and enters airways [Aspiration hazard - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List		
		Some Solvents		
SUBSTANCE NOTES: This is a diluent in the product.				

ETHYLHYDROXYETHYLCELLULOSE

ID: 9004-58-4

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:18:59	
%: 0.1000 - 0.8000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Viscosity modifier

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: This is a thickener in the product.

Section 3: Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	UL/GreenGuard Gold Certified	
COMPLIANCE TYPE: Third Party CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: UL Environment COMPLIANCE DETAILS: COMPLIANCE SCOPE: APPLICABLE FACILITIES: All. COMPLIANCE URL: https://api.stifirestop.com/resources/greenguard/sns-sealant-greenguard-gold-certification COMPLIANCE NOTES: TVOC <= 0.22 gm/m3 UL 2818 - 2013 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings	ISSUE DATE: 2021-01-27	EXPIRY DATE: No expiration
VOC CONTENT	SCAQMD Rule 1168 Adhesive and Sealant Applications - Adhesives for Wood Flooring, Rubber Floor, Ceramic Tile, Multipurpose Construction, Structural Glazing and Contact, as amended 1/7/05	
COMPLIANCE TYPE: Self-declared CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: Self-declared. COMPLIANCE DETAILS: COMPLIANCE SCOPE: APPLICABLE FACILITIES: All. COMPLIANCE URL: https://api.stifirestop.com/resources/safety-data-sheets/sns-smoke-n-sound-acoustical-sealant-safety-data-sheet COMPLIANCE NOTES: US EPA Method 24.	ISSUE DATE: 2024-04-30	EXPIRY DATE: No expiration
VOC CONTENT (AMENDED)	SCAQMD Rule 1168 Adhesive and Sealant Applications - Adhesives for Wood Flooring, Rubber Floor, Ceramic Tile, Multipurpose Construction, Structural Glazing and Contact, as amended 11/4/2022	
COMPLIANCE TYPE: Self-declared CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: Self-declared. COMPLIANCE DETAILS: COMPLIANCE SCOPE: APPLICABLE FACILITIES: All. COMPLIANCE URL: https://api.stifirestop.com/resources/safety-data-sheets/sns-smoke-n-sound-acoustical-sealant-safety-data-sheet COMPLIANCE NOTES: US EPA Method 24	ISSUE DATE: 2024-05-07	EXPIRY DATE: No expiration

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Specifications:

The smoke sealing caulk shall be a water based, high quality latex sealant and shall dry to a water resistant and flexible smoke barrier when dry. The sealant shall be tested for smoke sealing, noise abatement (acoustical) properties and shall meet Class A finish requirements when tested in accordance with ASTM E84 (UL723).

Specified Divisions:

Division 7; 07 90 00 Joint Protection

Division 7; 07 95 00 Expansion Control

Division 9; 09 20 00 Plaster and Gypsum Board

Division 9; 09 80 00 Acoustical Treatment

Features & Benefits:

Economical - high performance without the high price

- Water resistant - will not re-emulsify when dry
- Water-based - easy installation, cleanup, and disposal
- Remains flexible - allows movement
- Acoustically tested, reduces noise transmission
- Paintable when dry
- Safe, no solvents, no asbestos, no PCB's, no inorganic fibers
- Auto bonding
- Non-halogenated

MANUFACTURER INFORMATION

MANUFACTURER: **Specified Technologies Inc.**
ADDRESS: **210 Evans Way**
Somerville, NJ 08876
COUNTRY: **USA**

WEBSITE: **www.stifirestop.com**
CONTACT NAME: **George Gornick, LEED Green Associate**
TITLE: **Applications Engineer**
PHONE: **800-992-1180 Ext. 1013**
EMAIL: **ggornick@stifirestop.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold	Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold	Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold	Substances listed individually per threshold indicated per product

Nano	Composed of nano scale particles or nanotechnology
Third Party Verified	Verification by independent certifier approved by HPDC
Preparer	Third party preparer, if not self-prepared by manufacturer
Applicable facilities	Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.