

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 3.0, available on the HPDC website at: www.hpd-collaborative.org/hpd-3-0-standard

SPECSEAL® SERIES LC ENDOTHERMIC FIRESTOP SEALANT

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: The Calcium Carbonate portion of this product contains crystalline Silica as a residual.

OTHER PRODUCT NOTES: The Calcium Carbonate portion of this product contains crystalline Silica as a residual.

LIMESTONE, CALCIUM CARBONATEID: 1317-65-3

HAZARD DATA SOURCE:Pharos Chemical and Materials LibraryHAZARD SCREENING DATE:2025-11-04 8:18:13

%:30.0000 - 60.0000GreenScreen:BM-3dgRC:NoneNANO:NoSUBSTANCE ROLE:Filler

HAZARD TYPELIST NAME AND SOURCEWARNINGS

None foundNo warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGSLIST NAME AND SOURCENOTIFICATION

None foundNo listings found on Additional Hazard Lists

SUBSTANCE NOTES: This is a filler in the product.

2-PROPENOIC ACID, 2-METHYL-, POLYMER WITH BUTYL 2-PROPENOATE, ETHENYLBENZENE, 2-ETHYLHEXYL 2-PROPENOATE AND METHYL 2-METHYL-2-PROPENOATEID: 82539-93-3

HAZARD DATA SOURCE:Pharos Chemical and Materials LibraryHAZARD SCREENING DATE:2025-11-04 8:18:14

%:35.0000 - 50.0000GreenScreen:NoGSRC:NoneNANO:NoSUBSTANCE ROLE:Binder

HAZARD TYPELIST NAME AND SOURCEWARNINGS

None foundNo warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGSLIST NAME AND SOURCENOTIFICATION

None foundNo listings found on Additional Hazard Lists

SUBSTANCE NOTES: This is the binder in the product.

SpecSeal Series LC Endothermic Firestop Sealant

HPD v3.0 created via HPDC Builder Page 2 of 9

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-04 8:18:14	
%: 15.0000 - 25.0000	GreenScreen: BM-2	RC: None	NANO: No	SUBSTANCE ROLE: Flame retardant
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
SKI	GHS - New Zealand		Skin irritation category 2	
EYE	GHS - New Zealand		Eye irritation category 2	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)		C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2025	
			Children's Toy Products	
SUBSTANCE NOTES: This is a flame retardant in the product.				

SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC

ID: 64742-88-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-04 8:18:15	
%: 0.5000 - 2.5000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Carrier
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
END	TEDX - Potential Endocrine Disruptors		Potential Endocrine Disruptor	
MAM	EU - GHS (H-Statements) Annex 6 Table 3-1		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]	
MAM	EU - GHS (H-Statements) Annex 6 Table 3-1		H304 - May be fatal if swallowed and enters airways [Aspiration hazard - Category 1]	
MAM	GHS - Australia		H304 - May be fatal if swallowed and enters airways [Aspiration hazard - Category 1]	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
RESTRICTED LIST	Green Science Policy Institute (GSPI)		GSPI - Six Classes Precautionary List	
			Some Solvents	
SUBSTANCE NOTES: This is a carrier in the product.				

PROPYLENE GLYCOL

ID: 57-55-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-04 8:18:15	
%: 0.5000 - 1.5000	GreenScreen: BM-2	RC: None	NANO: No	SUBSTANCE ROLE: Anti-freeze

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Japan	H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List Antimicrobials
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List Some Solvents
SUBSTANCE NOTES: This is an anti-freeze agent in the product.		

ALCOHOLS, C8-22, ETHOXYLATED

ID: **Undisclosed**

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2025-11-04 8:18:13		
%: 0.5000 - 1.5000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Surfactant
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
SKI	GHS - Australia		H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]	
EYE	GHS - Australia		H318 - Causes serious eye damage [Serious eye damage/eye irritation - Category 1]	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	
SUBSTANCE NOTES: This is a surfactant in the product.				

FERRIC OXIDE

ID: **1309-37-1**

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-04 8:18:14	
%: 0.5000 - 1.5000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Pigment

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Japan	H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists
SUBSTANCE NOTES: This is a color pigment in the product.		

ETHYLHYDROXYETHYLCELLULOSE					ID: Undisclosed
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-04 8:18:14		
%: 0.2000 - 0.5000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Viscosity modifier	
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS			
None found		No warnings found on HPD Priority Hazard Lists			
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION			
None found		No listings found on Additional Hazard Lists			
SUBSTANCE NOTES: This is a thickener in the product.					

UNDISCLOSED					ID: Undisclosed
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-04 8:18:15		
%: 0.1000 - 0.2000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Stabilizer	

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
EYE	EU - GHS (H-Statements) Annex 6 Table 3-1	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
SKI	GHS - New Zealand	Skin irritation category 2
EYE	GHS - New Zealand	Eye irritation category 2
SKI	GHS - Australia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
EYE	GHS - Australia	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
EYE	GHS - Japan	H318 - Causes serious eye damage [Serious eye damage / eye irritation - Category 1]
SKI	GHS - Japan	H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]
AQU	GHS - New Zealand	Hazardous to the aquatic environment - chronic category 3
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: This is a stabilizer in the product.

Section 3: Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	UL/GreenGuard Gold Certified	
COMPLIANCE TYPE: Third Party CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: UL Environment COMPLIANCE DETAILS: COMPLIANCE SCOPE: APPLICABLE FACILITIES: All. COMPLIANCE URL: https://api.stifirestop.com/resources/greenguard/lc-greenguard-gold-certification COMPLIANCE NOTES: TVOC <= 0.22 gm/m3 UL 2818 - 2013 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings	ISSUE DATE: 2021-01-27	EXPIRY DATE: No expiration
VOC CONTENT	SCAQMD Rule 1168 Adhesive and Sealant Applications - Adhesives for Wood Flooring, Rubber Floor, Ceramic Tile, Multipurpose Construction, Structural Glazing and Contact, as amended 1/7/05	
COMPLIANCE TYPE: Self-declared CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: Self-declared. COMPLIANCE DETAILS: COMPLIANCE SCOPE: APPLICABLE FACILITIES: All. COMPLIANCE URL: https://api.stifirestop.com/resources/safety-data-sheets/lc-endothemic-firestop-sealant-safety-data-sheet COMPLIANCE NOTES: US EPA Method 24.	ISSUE DATE: 2020-08-11	EXPIRY DATE: No expiration

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Specifications:

The firestopping sealant shall be a one-part, latex-based compound. The sealant shall dry to form a flexible non-shrinking penetration seal and shall be capable of allowing pipe movement and shall contain no water soluble fillers, or inorganic fibers. The sealant shall be thixotropic and shall be capable of caulking or troweling onto vertical surfaces or overhead. The sealant shall be UL Certified and tested to the requirements of ASTM E814 (UL1479), ASTM E1966 (UL2079) and CAN/ULC-S115.

Special Divisions:

Division 7; 07 84 13 Penetration Firestopping
Division 7; 07 84 43 Joint Firestopping
Division 22; 22 00 00 Plumbing
Division 23; 23 00 00 HVAC
Division 26; 23 00 00 Electrical

Performance:

SpecSeal® LC Sealant is the basis for systems that meet the exact criteria of ASTM E1966 (UL2079) and CAN/ULC-S115 as well as the time-temperature requirements of ASTM E119. Tested systems will provide up to a 3 hour rating utilizing as little as 1/4" (6 mm) of sealant depth (1/2" (13 mm) for 4 hours). All tested systems have been cycled 500 times at total movement up to +/- 12.5% or 25% in compression only.

Features & Benefits:

- Water-based - easy installation, cleanup, & disposal
- Endothermic fillers - absorb heat & release water
- High solids formula - minimal shrinkage
- Paintable when dry
- Safe, low VOC's, no asbestos, no PCB's, no inorganic fibers
- Red color - easy identification and inspection
- Installer friendly - excellent caulking properties along with high build capabilities
- Excellent smoke seal
- Flexible
- Non-halogenated
- Auto bonding

MANUFACTURER INFORMATION

MANUFACTURER: **Specified Technologies Inc.**
ADDRESS: **210 Evans Way**
Somerville, NJ 08876
COUNTRY: **USA**

WEBSITE: **www.stifirestop.com**
CONTACT NAME: **George Gornick, LEED Green Associate**
TITLE: **Applications Engineer**
PHONE: **800-992-1180, Ext. 1013**
EMAIL: **ggornick@stifirestop.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.