

HPD UNIQUE IDENTIFIER: 28627

CLASSIFICATION: 07 84 53 Building Perimeter Firestopping

PRODUCT DESCRIPTION: SpecSeal® Safing Spray is a high solids, latex-based elastomeric coating specifically formulated for slab edge safing applications. Utilizing a premium latex binder system, it is totally resistant to water and will not re-emulsify after drying. Upon drying, it forms a flexible barrier against the spread of fire, hot gases, and smoke. It does not contain inorganic fibers, asbestos, or solvents. Applications: SpecSeal® Safing Spray is designed for use in curtain wall safing applications for perimeter fire barrier systems. Performance: SpecSeal® Safing Spray is applied over mineral wool safing. It is tested for 1, 2, 3, and 4 hour rated perimeter fire barrier systems in accordance with the Standard, ASTM E2307, “Standard Test Method for Determining the Fire Resistance of Perimeter Fire Barrier Systems Using Intermediate-Scale, Multi-Story Test Apparatus”. It complies with the time/temperature conditions of ASTM E119 (ANSI/UL263) and prevents ignition of cotton waste. It further complies with CAN/ULC-S101 and CAN/ULC-S115. Consult factory for individual system designs and application requirements.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities	<i>All Substances Above the Threshold Indicated Are:</i>
☐ Nested Materials Method	☐ 100 ppm	☒ Considered	Characterized ☐ Yes Ex/SC ☒ Yes ☐ No
☒ Basic Method	☒ 1,000 ppm	☐ Partially Considered	<i>% weight and role provided for all substances.</i>
Threshold Disclosed Per	☐ Per GHS SDS	☐ Not Considered	Screened ☐ Yes Ex/SC ☒ Yes ☐ No
☐ Material	☐ Other	Explanation(s) provided for Residuals/Impurities?	<i>All substances screened using Priority Hazard Lists with results disclosed.</i>
☒ Product		☒ Yes ☐ No	Identified ☐ Yes Ex/SC ☐ Yes ☒ No
			<i>One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

SPECSEAL® SAFING SPRAY [UNDISCLOSED NoGS LIMESTONE, CALCIUM CARBONATE BM-3dg UNDISCLOSED BM-2 | RES WATER BM-4 ALCOHOLS, C8-22, ETHOXYLATED LT-UNK PROPYLENE GLYCOL BM-2 | END ENGLISH FULLERS EARTH NoGS FERRIC OXIDE BM-1 | CAN HYDROTREATED HEAVY PARAFFINIC PETROLEUM DISTILLATES (MINERAL OIL) LT-1 | CAN | MUL]

Number of Greenscreen BM-4/BM3 contents ... 1

Contents highest concern GreenScreen Benchmark or List translator Score ... BM-1
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

None.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 30 Regulatory (g/l): 250
Does the product contain exempt VOCs: No
Are ultra-low VOC tints available: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified
VOC content: SCAQMD Rule 1168 Adhesive and Sealant Applications - Adhesives for Wood Flooring, Rubber Floor, Ceramic Tile, Multipurpose Construction, Structural Glazing and Contact, as amended 1/7/05

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1

Third Party Verified?

☐ Yes
☒ No

PREPARER: Self-Prepared

VERIFIER:
VERIFICATION #:

SCREENING DATE: 2022-06-07

PUBLISHED DATE: 2022-06-07

EXPIRY DATE: 2025-06-07

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

SPECSEAL® SAFING SPRAY

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: The Calcium Carbonate portion of this product contains residual crystalline silica.

OTHER PRODUCT NOTES: The Calcium Carbonate portion of this product contains residual crystalline silica.

UNDISCLOSED

ID: Undisclosed

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2022-06-07 5:37:53

?: 40.0000 - 60.0000

GS: NoGS

RC: None

NANO: No

SUBSTANCE ROLE: Binder

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This material is the binder in the product.

LIMESTONE, CALCIUM CARBONATE

ID: 1317-65-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2022-06-07 5:37:53

?: 25.0000 - 45.0000

GS: BM-3dg

RC: None

NANO: No

SUBSTANCE ROLE: Filler

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: This material is used as a filler in the product.

UNDISCLOSED

ID: Undisclosed

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2022-06-07 5:37:54

?: 10.0000 - 20.0000

GS: BM-2

RC: None

NANO: No

SUBSTANCE ROLE: Flame retardant

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

RES

AOEC - Asthmagens

Asthmagen (Rs) - sensitizer-induced

SUBSTANCE NOTES: This material is a flame retardant in the product.

WATER

ID: 7732-18-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2022-06-07 5:37:54

%: 4.0000 - 8.0000		GS: BM-4	RC: None	NANO: No	SUBSTANCE ROLE: Carrier
HAZARD TYPE		AGENCY AND LIST TITLES		WARNINGS	
None found		No warnings found on HPD Priority Hazard Lists			
SUBSTANCE NOTES: This material is the carrier in the product.					

ALCOHOLS, C8-22, ETHOXYLATED					ID: 69013-19-0
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2022-06-07 5:37:55		
%: 1.0000 - 2.0000	GS: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Surfactant	
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS			
None found		No warnings found on HPD Priority Hazard Lists			
SUBSTANCE NOTES: This material is a surfactant in the product.					

PROPYLENE GLYCOL					ID: 57-55-6	
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2022-06-07 5:37:55			
%: 1.0000 - 2.0000		GS: BM-2		RC: None	NANO: No	SUBSTANCE ROLE: Anti-freeze
HAZARD TYPE		AGENCY AND LIST TITLES			WARNINGS	
END		TEDX - Potential Endocrine Disruptors			Potential Endocrine Disruptor	
SUBSTANCE NOTES: This material is for freeze protection of the product.						

ENGLISH FULLERS EARTH					ID: 8031-18-3
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2022-06-07 5:37:56		
%: 1.0000 - 4.0000		GS: NoGS		RC: None NANO: No SUBSTANCE ROLE: Viscosity modifier	
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS		
None found			No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: This material is used to thicken the product.					

FERRIC OXIDE				ID: 1309-37-1
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-07 5:37:56		
%: 1.0000 - 3.0000	GS: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Pigment
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
SUBSTANCE NOTES: This material is used to add color to the product.				

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-07 5:37:57			
%: 0.1000 - 0.2000		GS: LT-1	RC: None	NANO: No	SUBSTANCE ROLE: Defoamer
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS		
CAN	EU - REACH Annex XVII CMRs		Carcinogen Category 2 - Substances which should be regarded as if they are Carcinogenic to man		
CAN	EU - Annex VI CMRs		Carcinogen Category 1B - Presumed Carcinogen based on animal evidence		
MUL	ChemSec - SIN List		CMR - Carcinogen, Mutagen &/or Reproductive Toxicant		
CAN	GHS - Australia		H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]		
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1		H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]		
SUBSTANCE NOTES: This material prevents foaming during application.					

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	UL/GreenGuard Gold Certified		
CERTIFYING PARTY: Third Party APPLICABLE FACILITIES: All. CERTIFICATE URL: https://api.stifirestop.com/resources/greenguard/sfs-greenguard-gold-certification	ISSUE DATE: 2021-01-27	EXPIRY DATE:	CERTIFIER OR LAB: UL Environment
CERTIFICATION AND COMPLIANCE NOTES: TVOC <= 0.22 gm/m3 UL 2818 - 2013 Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings			
VOC CONTENT	SCAQMD Rule 1168 Adhesive and Sealant Applications - Adhesives for Wood Flooring, Rubber Floor, Ceramic Tile, Multipurpose Construction, Structural Glazing and Contact, as amended 1/7/05		
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: All. CERTIFICATE URL: https://api.stifirestop.com/resources/safety-data-sheets/sfs-safing-spray-safety-data-sheet	ISSUE DATE: 2018-07-03	EXPIRY DATE:	CERTIFIER OR LAB: Self-declared.
CERTIFICATION AND COMPLIANCE NOTES: Per US EPA Method 24.			

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Specifications:

The perimeter fire barrier spray shall be a water-based, non-halogenated elastomeric coating containing no solvents, inorganic fibers, or asbestos. The coating shall dry to form a flexible, water resistant film and adhere to all common construction surfaces. The Shore A hardness of the dried coating shall be minimum 65. The coating shall be UL Certified and listed in the XHDG Category for Perimeter Fire-Containment Systems. The approved coating shall be SpecSeal® Safing Spray.

Specified Divisions:

Division 7; 07 84 00 Firestopping,
Division 7; 07 84 53 Building Perimeter Firestopping
Division 8; 08 44 00 Curtain Wall and Glazed Assemblies

Performance:

SpecSeal® Safing Spray is applied over mineral wool safing. It is tested for 1, 2, 3, and 4 hour rated perimeter fire barrier systems in accordance with the Standard, ASTM E2307, "Standard Test Method for Determining the Fire Resistance of Perimeter Fire Barrier Systems Using Intermediate-Scale, Multi-Story Test Apparatus". It complies with the time/temperature conditions of ASTM E119 (ANSI/UL263) and prevents ignition of cotton waste. It further complies with CAN/ULCS101 and CAN/ULCS115. Consult factory for individual system designs and application requirements.

Features & Benefits:

- Optimized for curtain wall conditions
- Tougher polymer can stand up to jobsite rigors
- Fast drying latex binder base
- Easy cleanup with water
- Approved with penetrants in safing slot
- Allows for vertical application for column or shear wall interfaces
- UL Certified
- Safe, no solvents, no asbestos, no PCB's, no inorganic fibers
- Non-halogenated
- Auto bonding
- Paintable when dry

MANUFACTURER INFORMATION

MANUFACTURER: Specified Technologies Inc.
ADDRESS: 210 Evans Way
 Somerville NJ 08876, USA
WEBSITE: www.stifirestop.com

CONTACT NAME: George Gornick, LEED Green Associate
TITLE: Applications Engineer
PHONE: 800-992-1180 Ext. 1013
EMAIL: ggornick@stifirestop.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
BM-2 Benchmark 2 (use but search for safer substitutes)	
BM-1 Benchmark 1 (avoid - chemical of high concern)	
BM-U Benchmark Unspecified (due to insufficient data)	
LT-P1 List Translator Possible 1 (Possible Benchmark-1)	NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.