

HPD UNIQUE IDENTIFIER: 435671915520
CLASSIFICATION: 08 14 00 Wood Doors
PRODUCT DESCRIPTION: This HPD covers Lambton Doors' Envirodesign™ series of 5-ply doors with a particleboard core. Specifically, it includes the following product models: 5-FSPC-EME/ECE/EBE, 5-UFPC-EME/ECE/EBE, 5-STC27-EME/ECE/EBE, 5-FS8300-EME/ECE/EBE, 5-UF8300-EME/ECE/EBE, 5 UF8500 EME/ECE, and 5 FS8500 EME/ECE. Please note that this HPD does not cover jambs or fixtures.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	
☒ Nested Materials Method	☐ 100 ppm	Completed in 4 of 8 Materials	<i>For all contents above the threshold, the manufacturer has:</i>
☐ Basic Method	☒ 1,000 ppm	Explanation(s) provided for Residuals/Impurities?	Characterized ☒ Yes ☐ No
Threshold Disclosed Per	☐ Per GHS SDS		<i>Provided weight and role.</i>
☐ Material	☐ Other	☒ Yes ☐ No	Screened ☒ Yes ☐ No
☒ Product			<i>Provided screening results using HPDC-approved methods.</i>
			Identified ☐ Yes ☒ No
			<i>Provided name and CAS RN or other identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

PARTICLEBOARD [WOOD FIBER UREA FORMALDEHYDE LT-P1]
SKI **WATER BM-4 MELAMINE-CELLULOSE UREA LT-UNK** EYE
SLACK WAX (PETROLEUM) LT-1 CAN | MUL | DEV] **CROSSBAND HDF [WOOD DUST UREA FORMALDEHYDE LT-P1]** SKI **MELAMINE LT-P1** END | CAN | MAM **SLACK WAX (PETROLEUM) LT-1** CAN | MUL | DEV] **STILES AND RAILS [WOOD DUST POLYMETHYLENE POLYPHENYL ISOCYANATE LT-UNK** CAN | RES | EYE | SKI | MAM] **STILES AND RAILS (ALT) [HARDWOOD WATER BM-4 PHENOL-FORMALDEHYDE RESIN LT-P1]** **VENEER [WOOD]** **HARDWOOD SLATS [WOOD (HARDWOOD)]** **ADHESIVES [UNDISCLOSED LT-UNK UNDISCLOSED BM-4]** **UV FINISHES [BISPHENOL A-EPICHLOROHYDRIN ACRYLATE BM-1** MUL **DIPROPYLENE GLYCOL DIACRYLATE LT-UNK** SKI | EYE **TITANIUM DIOXIDE BM-1** CAN | END | MAM **LIMESTONE BM-3dg** **ETHOXYLATED TRIMETHYLOLPROPANE TRIACRYLATE LT-P1** SKI | EYE | AQU **1,6-HEXANEDIOL DIACRYLATE LT-P1** SKI | MUL | EYE | AQU]

Number of Greenscreen BM-4/BM3 contents ... 4
Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1, BM-1, LT-1
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Special Conditions applied: [BiologicalMaterial]

Special Conditions materials are present in the product, specifically biological materials. The reporting guidelines for biological materials (SCBioMats/2023-07-20) have been followed, and the full composition has been provided accordingly. However, due to confidentiality reasons, certain substances are not disclosed by name or CAS number.

PFAS DETAILS:

PFAS Attestation states "Unknown if product contains PFAS"

Attestation:

DJB

2025-04-09

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.
VOC emissions: CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario
LCA: Environmental Product Declaration (EPD) by CSA Group

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Option 1.
Pre-checked for LEED v4.1 Option 1.

☐ Yes

☒ No

VERIFIER:

VERIFICATION #:

PUBLISHED DATE: 2025-05-20

EXPIRY DATE: 2028-05-20

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

PARTICLEBOARD

%: 67.2600

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No

MATERIAL TYPE: Wood Dust, Fiber or Chips

RESIDUALS AND IMPURITIES NOTES: According to the supplier's information, no evaluation of residuals or impurities has been conducted for this material.

OTHER MATERIAL NOTES: According to the supplier's information, particleboard is primarily composed of cellulosic materials (typically wood), generally in the form of discrete particles, as opposed to fibers, bonded together with a resin system cured under heat and pressure.

WOOD FIBER

ID: Biological Material

HAZARD DATA SOURCE: HPDC Special Conditions Policy

%: 82.9000 - 85.9000

GreenScreen: Not Required

RC: PreC

NANO: No

MATERIAL ROLE: Structure component

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

Hazard Screening is not applicable to this Special Condition

BIOLOGICAL MATERIALS CATEGORY: Tree-based materials

INGREDIENT DESCRIPTION: Wood fiber refers to the elongated cells derived from wood, typically obtained through mechanical or chemical processing, and used as a raw material in the production of panels, paper, or composite materials.

MATERIAL CONTENT NOTES: Pre-consumer recycled content includes fibers (such as scraps, trimmings, and cuttings) generated as by-products of manufacturing and converting processes of primary wood products. Examples in this category include planer shavings, plytrim, sawdust, fines, chips, and bagasse.

This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials.

UREA FORMALDEHYDE

ID: 9011-05-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-05-20 5:44:03

%: 7.3000 - 7.6000

GreenScreen: LT-P1

RC: None

NANO: No

SUBSTANCE ROLE: Binder

HAZARD TYPE

LIST NAME AND SOURCE

WARNINGS

SKI

GHS - New Zealand

Skin sensitisation category 1

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Perkins+Will (P+W)	P&W - Precautionary List Precautionary list of substances recommended for avoidance
RESTRICTED LIST	International Living Future Institute (ILFI)	Living Building Challenge 4.0 - Red List of Materials & Chemicals - Effective February 1, 2025 Red List substances to avoid in Living Building Challenge V4.0 projects
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2024 All Products

SUBSTANCE NOTES: Urea formaldehyde (UF) is a thermosetting resin synthesized from urea and formaldehyde through addition and condensation reactions. It is widely used in adhesives, plywood, particleboard, MDF, and molded products. The weight percentage range is used to account for product variability and/or to maintain confidentiality regarding the material composition in the manufacturing process.

UREA, POLYMER WITH FORMALDEHYDE AND 1,3,5-TRIAZINE-2,4,6-TRIAMINE

ID: 25036-13-9

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2025-05-20 5:44:04**

%: **7.3000 - 7.6000 ALT** GreenScreen: **LT-UNK** RC: **None** NANO: **No** SUBSTANCE ROLE: **Binder**

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Perkins+Will (P+W)	P&W - Precautionary List Precautionary list of substances recommended for avoidance
RESTRICTED LIST	International Living Future Institute (ILFI)	Living Building Challenge 4.0 - Red List of Materials & Chemicals - Effective February 1, 2025 Red List substances to avoid in Living Building Challenge V4.0 projects

SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain confidentiality regarding the material composition in the manufacturing process.

ALTERNATE: This substance is an alternate substance to Urea formaldehyde.

WATER

ID: 7732-18-5

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library** HAZARD SCREENING DATE: **2025-05-20 5:44:04**

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions Exempted from REACH Annex IV listing due to intrinsic safety
SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.		

MELAMINE-CELLULOSE

ID: Biological Material

HAZARD DATA SOURCE: HPDC Special Conditions Policy				
%: 0.0000 - 3.2000	GreenScreen: Not Required	RC: None	NANO: No	MATERIAL ROLE: Polymer species
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS	
Hazard Screening is not applicable to this Special Condition				
BIOLOGICAL MATERIALS CATEGORY: Tree-based materials				
INGREDIENT DESCRIPTION: Melamine-cellulose is a composite material combining the strength of melamine resin with the natural fibers of cellulose. It offers durability, heat resistance, ease of maintenance, and is commonly used in decorative panels and furniture composites.				
MATERIAL CONTENT NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.				
This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials.				

UREA

ID: 57-13-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:05	
%: 0.7000 - 0.8000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Scavenger
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
EYE	GHS - New Zealand	Eye irritation category 2		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List Antimicrobials		

SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

SLACK WAX (PETROLEUM)

ID: 64742-61-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-05-20 5:44:05

%, 0.0000 - 0.3000

GreenScreen: LT-1

RC: None

NANO: No

SUBSTANCE ROLE: Water resistance

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	EU - Annex VI CMRs	Carcinogen Category 1B - Presumed Carcinogen based on animal evidence
MUL	ChemSec - SIN List	CMR - Carcinogen, Mutagen &/or Reproductive Toxicant
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
CAN	GHS - Australia	H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1	H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]
DEV	GHS - Australia	H361d - Suspected of damaging the unborn child [Reproductive toxicity - Category 2]
CAN	EU - REACH Annex XVII CMRs	Carcinogens: Category 1B
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Children's Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Formulated Consumer Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2024 All Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2024 Cosmetics and Personal Care Products

SUBSTANCE NOTES: Slack Wax is a semi-solid byproduct of petroleum refining, composed of paraffin and oil. It is primarily used in industrial applications such as candle manufacturing, rubber processing, polishes, coatings, and moisture-resistant materials. The weight percentage range is used to account for product variability and/or to maintain confidentiality regarding the material composition in the manufacturing process.

CROSSBAND HDF		%: 20.9400
PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No	MATERIAL TYPE: Wood Dust, Fiber or Chips
RESIDUALS AND IMPURITIES NOTES: According to the supplier's information, no evaluation of residuals or impurities has been conducted for this material.		
OTHER MATERIAL NOTES: High-density fiberboard (HDF) without any added formaldehyde.		

WOOD DUST

ID: Biological Material

HAZARD DATA SOURCE: HPDC Special Conditions Policy				
%: 79.0000 - 84.0000	GreenScreen: Not Required	RC: None	NANO: No	MATERIAL ROLE: Structure component
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS	
Hazard Screening is not applicable to this Special Condition				
BIOLOGICAL MATERIALS CATEGORY: Tree-based materials				
INGREDIENT DESCRIPTION: Wood dust is a fine powder resulting from wood processing, such as sawing, sanding, or milling. It is often used in composite materials like particleboard or as a filler in various products.				
MATERIAL CONTENT NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.				
This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials.				

UREA FORMALDEHYDE

ID: 9011-05-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:04	
%: 14.0000 - 18.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
SKI	GHS - New Zealand		Skin sensitisation category 1	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
RESTRICTED LIST	Perkins+Will (P+W)		P&W - Precautionary List	
			Precautionary list of substances recommended for avoidance	
RESTRICTED LIST	International Living Future Institute (ILFI)		Living Building Challenge 4.0 - Red List of Materials & Chemicals - Effective February 1, 2025	
			Red List substances to avoid in Living Building Challenge V4.0 projects	
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)		C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2024	
			All Products	

SUBSTANCE NOTES: Urea formaldehyde (UF) is a thermosetting resin synthesized from urea and formaldehyde through addition and condensation reactions. It is widely used in adhesives, plywood, particleboard, MDF, and molded products. The weight percentage range is used to account for product variability and/or to maintain confidentiality regarding the material composition in the manufacturing process.

MELAMINE

ID: 108-78-1

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-05-20 5:44:05

%: 1.5000 - 2.5000

GreenScreen: LT-P1

RC: None

NANO: No

SUBSTANCE ROLE: Intumescent

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
CAN	IARC	Group 2b - Possibly carcinogenic to humans
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]
CAN	GHS - Japan	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]
CAN	EU - Annex VI CMRs	Carcinogen Category 2 - Suspected human Carcinogen
CAN	GHS - Australia	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]
MAM	EU - SVHC List	Equivalent Concern - Prioritization List
MAM	EU - SVHC List	Equivalent Concern - Candidate List
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022
		Children's Products

SUBSTANCE NOTES: Melamine is a chemical compound used primarily in the production of resins, which are then used in laminates, adhesives, and coatings. The weight percentage range is used to account for product variability and/or to maintain confidentiality regarding the material composition in the manufacturing process.

SLACK WAX (PETROLEUM)

ID: 64742-61-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-05-20 5:44:06

%: 0.0000 - 1.0000

GreenScreen: LT-1

RC: None

NANO: No

SUBSTANCE ROLE: Water resistance

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	EU - Annex VI CMRs	Carcinogen Category 1B - Presumed Carcinogen based on animal evidence
MUL	ChemSec - SIN List	CMR - Carcinogen, Mutagen &/or Reproductive Toxicant
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
CAN	GHS - Australia	H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1	H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]
DEV	GHS - Australia	H361d - Suspected of damaging the unborn child [Reproductive toxicity - Category 2]
CAN	EU - REACH Annex XVII CMRs	Carcinogens: Category 1B

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Children's Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Formulated Consumer Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2024 All Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2024 Cosmetics and Personal Care Products

SUBSTANCE NOTES: Slack Wax is a semi-solid byproduct of petroleum refining, composed of paraffin and oil. It is primarily used in industrial applications such as candle manufacturing, rubber processing, polishes, coatings, and moisture-resistant materials. The weight percentage range is used to account for product variability and/or to maintain confidentiality regarding the material composition in the manufacturing process.

STILES AND RAILS

%: 2.2400 - 12.5800

PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No	MATERIAL TYPE: Wood Dust, Fiber or Chips
-----------------------------	---	--

RESIDUALS AND IMPURITIES NOTES: According to the supplier's information, no evaluation of residuals or impurities has been conducted for this material. The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

OTHER MATERIAL NOTES: Stiles and rails are primarily made of structural composite lumber.

WOOD DUST

ID: Biological Material

HAZARD DATA SOURCE: HPDC Special Conditions Policy

%: 93.0000 - 96.0000 GreenScreen: Not Required RC: None NANO: No MATERIAL ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
Hazard Screening is not applicable to this Special Condition		

BIOLOGICAL MATERIALS CATEGORY: Tree-based materials

INGREDIENT DESCRIPTION: Wood dust is a fine powder resulting from wood processing, such as sawing, sanding, or milling. It is often used in composite materials like particleboard or as a filler in various products.

MATERIAL CONTENT NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials.

POLYMETHYLENE POLYPHENYL ISOCYANATE

ID: 9016-87-9

HAZARD DATA SOURCE: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2025-05-20 5:44:06

%: 3.0000 - 6.0000 GreenScreen: LT-UNK RC: None NANO: No SUBSTANCE ROLE: Binder

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels
RES	MAK	Sensitizing Substance Sah - Danger of airway & skin sensitization
EYE	GHS - New Zealand	Eye irritation category 2
SKI	GHS - Australia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
EYE	GHS - Australia	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
CAN	GHS - Japan	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1
MAM	GHS - Japan	H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]
MAM	GHS - New Zealand	Acute inhalation toxicity category 2
MAM	Québec CSST - WHMIS 1988	Class D1A - Very toxic material causing immediate and serious toxic effects
MAM	GHS - Australia	H330 - Fatal if inhaled [Acute toxicity (inhalation) - Category 1 or 2]
MAM	GHS - Japan	H330 - Fatal if inhaled [Acute toxicity (inhalation: dust, mist) - Category 2]
CAN	GHS - Australia	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Perkins+Will (P+W)	P&W - Precautionary List Precautionary list of substances recommended for avoidance
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CP II)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Formulated Consumer Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CP II)	C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2024 All Products

SUBSTANCE NOTES: Polymethylene polyphenyl isocyanate (PAPI) is a type of polyisocyanate used in the production of polyurethanes, particularly for rigid foams and insulation materials. The weight percentage range is used to account for product variability and/or to maintain confidentiality regarding the material composition in the manufacturing process.

STILES AND RAILS (ALT) %: 5.9100 - 12.2800

PRODUCT THRESHOLD: 1000 ppm RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No MATERIAL TYPE: Wood or Lumber

RESIDUALS AND IMPURITIES NOTES: According to the supplier's information, no evaluation of residuals or impurities has been conducted for this material. The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

OTHER MATERIAL NOTES: Stiles and rails (LVL) are primarily made of structural composite lumber.

HARDWOOD ID: Biological Material

HAZARD DATA SOURCE: HPDC Special Conditions Policy

%: 90.9000 GreenScreen: Not Required RC: None NANO: No MATERIAL ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
Hazard Screening is not applicable to this Special Condition		

BIOLOGICAL MATERIALS CATEGORY: Tree-based materials

INGREDIENT DESCRIPTION: Hardwood refers to wood from deciduous trees, typically used in composite panels for its density and strength. It is a natural material composed primarily of cellulose, hemicellulose, and lignin.

MATERIAL CONTENT NOTES: As a biological material, the exact composition of hardwood can vary depending on tree species and growing conditions.

This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials.

WATER ID: 7732-18-5

HAZARD DATA SOURCE: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2025-05-20 5:44:07

%: 3.5000 GreenScreen: BM-4 RC: None NANO: No SUBSTANCE ROLE: Filler

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions Exempted from REACH Annex IV listing due to intrinsic safety

SUBSTANCE NOTES: Water acts as a dispersing agent and helps control resin viscosity during particleboard manufacturing. It also aids in heat transfer during pressing but is mostly evaporated and not present in the final product.

PHENOL-FORMALDEHYDE RESIN

ID: 9003-35-4

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-05-20 5:44:06

%: 3.4000

GreenScreen: LT-P1

RC: None

NANO: No

SUBSTANCE ROLE: Binder

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	International Living Future Institute (ILFI)	Living Building Challenge 4.0 - Red List of Materials & Chemicals - Effective February 1, 2025 Red List substances to avoid in Living Building Challenge V4.0 projects

SUBSTANCE NOTES: Phenol-formaldehyde resin is a thermosetting polymer made by reacting phenol with formaldehyde. It is known for its high mechanical strength, heat resistance, and durability.

VENEER

%: 1.9100

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Wood or Lumber

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities were considered.

OTHER MATERIAL NOTES: Veneer are available in a multitude of wood species, but Maple has been chosen as baseline scenario.

WOOD

ID: Biological Material

HAZARD DATA SOURCE: HPDC Special Conditions Policy

%: 100.0000

GreenScreen: Not Required

RC: None

NANO: No

MATERIAL ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
		Hazard Screening is not applicable to this Special Condition

BIOLOGICAL MATERIALS CATEGORY: Tree-based materials

INGREDIENT DESCRIPTION: Wood is a natural material known for its strength, durability, and thermal insulation. It is composed of cellulose fibers and is hygroscopic, absorbing and releasing moisture to balance humidity.

MATERIAL CONTENT NOTES: Several types of wood can be used, but Maple has been chosen as the baseline scenario.

This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials.

HARDWOOD SLATS

%: 1.4700

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No

MATERIAL TYPE: Wood or Lumber

RESIDUALS AND IMPURITIES NOTES: According to the supplier's information, no evaluation of residuals or impurities has been conducted for this material.

OTHER MATERIAL NOTES: Hardwood slats are made from various hardwood species; however, maple has been selected as the baseline scenario.

WOOD (HARDWOOD)

ID: Biological Material

HAZARD DATA SOURCE: HPDC Special Conditions Policy

%: 100.0000

GreenScreen: Not Required

RC: None

NANO: No

MATERIAL ROLE: Structure component

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

Hazard Screening is not applicable to this Special Condition

BIOLOGICAL MATERIALS CATEGORY: Tree-based materials

INGREDIENT DESCRIPTION: Wood is a natural material known for its strength, durability, and thermal insulation. It is composed of cellulose fibers and is hygroscopic, absorbing and releasing moisture to balance humidity.

MATERIAL CONTENT NOTES: Several types of wood can be used, but Maple has been chosen as the baseline scenario.

This disclosure does not provide information on allergens, hyper-accumulation of metals, production of any toxic substances during normal metabolic activities, pesticides, and other potential hazards or sources of hazards which may be found in certain biological materials.

ADHESIVES

%: 0.9400

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: According to the supplier's information, no evaluation of residuals or impurities has been conducted for this material.

OTHER MATERIAL NOTES: Adhesives are used throughout the production line for assembly. However, information regarding the adhesives used in the process is confidential.

UNDISCLOSED				ID: Undisclosed
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:07	
%: 75.0000 - 85.0000 ALT	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Adhesive
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor		
SKI	GHS - New Zealand	Skin corrosion category 1C		
EYE	GHS - New Zealand	Serious eye damage category 1		
SKI	GHS - Australia	H314 - Causes severe skin burns and eye damage [Skin corrosion/irritation - Category 1A or 1B or 1C]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes Precautionary List		
		Antimicrobials		
SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.				
ALTERNATE: This substance is an alternate substance to Substance 1.				

UNDISCLOSED				ID: Undisclosed
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:08	
%: 30.0000 - 60.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Adhesive
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.				

UNDISCLOSED				ID: Undisclosed
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:09	
%: 40.0000 - 60.0000	GreenScreen: BM-4	RC: None	NANO: No	SUBSTANCE ROLE: Solvent

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions Exempted from REACH Annex IV listing due to intrinsic safety
SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.		

UV FINISHES	%: 0.5000	
PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Polymeric Material
RESIDUALS AND IMPURITIES NOTES: Residuals and impurities were considered.		
OTHER MATERIAL NOTES: UV cured finishes (100% solids). Inventory of substances based on MSDS of all four layers of product (1 layer = 1 UV curable product, 4 layers (4 products) in total). All products have been merged into one material to simplify the inventory.		

BISPHENOL A-EPICHLOROHYDRIN ACRYLATE				ID: 55818-57-0
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:09	
%: 1.0000 - 40.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Film former
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
MUL	German FEA - Substances Hazardous to Waters		Class 3 - Severe Hazard to Waters	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)		C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022	
			Core Restrictions	
RESTRICTED LIST	International Living Future Institute (ILFI)		Living Building Challenge 4.0 - Red List of Materials & Chemicals - Effective February 1, 2025	
			Red List substances to avoid in Living Building Challenge V4.0 projects	
SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.				

TRIPROPYLENE GLYCOL DIACRYLATE				ID: 42978-66-5
HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2025-05-20 5:44:07		
%: 1.0000 - 40.0000 ALT	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Monomer

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
SKI	MAK	Sensitizing Substance Sh - Danger of skin sensitization
MUL	German FEA - Substances Hazardous to Waters	Class 3 - Severe Hazard to Waters
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
EYE	EU - GHS (H-Statements) Annex 6 Table 3-1	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
AQU	EU - GHS (H-Statements) Annex 6 Table 3-1	H411 - Toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 2]
SKI	GHS - New Zealand	Skin irritation category 2
EYE	GHS - New Zealand	Eye irritation category 2
SKI	GHS - Australia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
EYE	GHS - Australia	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
SKI	GHS - New Zealand	Skin sensitisation category 1
AQU	GHS - New Zealand	Hazardous to the aquatic environment - chronic category 2
AQU	GHS - Australia	H411 - Toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 2]
AQU	GHS - Japan	H401 - Toxic to aquatic life [Hazardous to the aquatic environment (acute) - Category 2]
AQU	GHS - Japan	H411 - Toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 2]
EYE	GHS - Japan	H319 - Causes serious eye irritation [Serious eye damage / eye irritation - Category 2A]

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

ALTERNATE: This substance is an alternate substance to Bisphenol A-epichlorohydrin acrylate.

DIPROPYLENE GLYCOL DIACRYLATE				ID: 57472-68-1
HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2025-05-20 5:44:08		
%: 0.0000 - 40.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Polymer species

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
SKI	GHS - New Zealand	Skin irritation category 2
EYE	GHS - New Zealand	Eye irritation category 2
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

TITANIUM DIOXIDE

ID: 13463-67-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2025-05-20 5:44:08

%: 0.0000 - 30.0000

GreenScreen: BM-1

RC: None

NANO: No

SUBSTANCE ROLE: Pigment

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources
CAN	MAK	Carcinogen Group 3A - Evidence of carcinogenic effects but not sufficient to establish MAK/BAT value
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
CAN	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels
CAN	IARC	Group 2b - Possibly carcinogenic to humans
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]
CAN	GHS - Japan	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Children's Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Formulated Consumer Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.0 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Cosmetics & Personal Care Products
POSITIVE LIST	US Environmental Protection Agency (US EPA)	US EPA - DfE Safer Chemicals Ingredients list (SCIL) Colorants - Green Circle (Verified Low Concern)
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2024 Cosmetics and Personal Care Products

SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

LIMESTONE				ID: 1317-65-3	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:09		
%: 0.0000 - 30.0000	GreenScreen: BM-3dg	RC: None	NANO: No	SUBSTANCE ROLE: Filler	
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS			
None found		No warnings found on HPD Priority Hazard Lists			
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION			
None found		No listings found on Additional Hazard Lists			
SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.					

ETHOXYLATED TRIMETHYLOLPROPANE TRIACRYLATE					ID: 28961-43-5
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:09		
%: 0.0000 - 30.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Binder	

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
SKI	GHS - New Zealand	Skin irritation category 2
EYE	GHS - New Zealand	Serious eye damage category 1
SKI	GHS - New Zealand	Skin sensitisation category 1
AQU	GHS - New Zealand	Hazardous to the aquatic environment - chronic category 2
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

1,6-HEXANEDIOL DIACRYLATE
ID: 13048-33-4

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-05-20 5:44:08	
%: 0.0000 - 30.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Solvent
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
SKI	MAK	Sensitizing Substance Sh - Danger of skin sensitization		
MUL	German FEA - Substances Hazardous to Waters	Class 3 - Severe Hazard to Waters		
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]		
EYE	EU - GHS (H-Statements) Annex 6 Table 3-1	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]		
SKI	GHS - New Zealand	Skin irritation category 2		
EYE	GHS - New Zealand	Eye irritation category 2		
SKI	GHS - Australia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]		
EYE	GHS - Australia	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]		
SKI	GHS - New Zealand	Skin sensitisation category 1		
AQU	GHS - Japan	H400 - Very toxic to aquatic life [Hazardous to the aquatic environment (acute) - Category 1]		
AQU	GHS - Japan	H410 - Very toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: The weight percentage range is used to account for product variability and/or to maintain the confidentiality of the material composition in the manufacturing process.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2025-03-13 00:00:00	CERTIFIER OR LAB: Intertek
APPLICABLE FACILITIES: All	EXPIRY DATE: 2026-03-21 00:00:00	Testing Services NA, Inc.
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Certificate Number: CA-10422-2025a		

LCA	Environmental Product Declaration (EPD) by CSA Group	
CERTIFYING PARTY: Third Party	ISSUE DATE:	CERTIFIER OR
APPLICABLE FACILITIES: All	2021-12-17	LAB: Vertima Inc
CERTIFICATE URL: https://www.lambtondoors.com/wp-content/uploads/2022/01/PORTES_LAMBTON_DEP_%C3%82me_en_bois_PC_8300_SCL_1642432211.pdf	00:00:00	
	EXPIRY DATE:	
	2026-12-16	
	00:00:00	
CERTIFICATION AND COMPLIANCE NOTES:		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

ALL ACCESSORIES
MANUFACTURER (OR GENERIC): Generic
HPD URL: No HPD available
ACCESSORY TYPE: Other
CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: Please consult Lambton Doors' website for more information on available accessories: http://www.lambtondoors.com/architects-space/technical-space/options-and-accessories/

Section 5: General Notes

See INVENTORY AND SCREENING NOTES.

MANUFACTURER INFORMATION

MANUFACTURER: **Lambton Doors**
ADDRESS: **235 2nd Avenue**
Lambton, Quebec G0M 1H0
COUNTRY: **Canada**

WEBSITE: **www.lambtondoors.com**
CONTACT NAME: **Caroline Duclos**
TITLE: **Technical coordinator**
PHONE: **1 800 463.3124 #2388**
EMAIL: **caroline.duclos@lambtondoors.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold	Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold	Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold	Substances listed individually per threshold indicated per product

Nano	Composed of nano scale particles or nanotechnology
Third Party Verified	Verification by independent certifier approved by HPDC
Preparer	Third party preparer, if not self-prepared by manufacturer
Applicable facilities	Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and

