

HPD UNIQUE IDENTIFIER: 28618
CLASSIFICATION: 09 80 00 Acoustic Treatment
PRODUCT DESCRIPTION: Designed using RPG's powerful shape optimization technology which optimizes sound diffusion while providing a given shape motif. The organic and modern contoured surface creates an asymmetric tile designed to provide a more uniform sound field through mid and high-frequency diffusion. At the same time, the non-combustible glass fiber reinforced concrete (GFRG) construction limits the amount of sound energy removed by absorption. The standard tiles are nom. 24" x 24" x 4" deep and come in a natural/raw GFRG finish to be painted on-site or factory color-matched to any paint specification.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities	All Substances Above the Threshold Indicated Are:	
☒ Nested Materials Method	☐ 100 ppm	Considered in 1 of 1 Materials	Characterized	☐ Yes Ex/SC ☒ Yes ☐ No
☐ Basic Method	☒ 1,000 ppm	Explanation(s) provided for Residuals/Impurities? ☒ Yes ☐ No	% weight and role provided for all substances.	
Threshold Disclosed Per	☐ Per GHS SDS		Screened	☐ Yes Ex/SC ☒ Yes ☐ No
☐ Material	☐ Other		All substances screened using Priority Hazard Lists with results disclosed.	
☒ Product			Identified	☐ Yes Ex/SC ☒ Yes ☐ No
			All substances disclosed by Name (Specific or Generic) and Identifier.	

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | **SUBSTANCE** | *RESIDUAL OR IMPURITY*
GREENSCREEN SCORE | HAZARD TYPE
FORMGLAS GFRG, MOLDED GLASS FIBER REINFORCED GYPSUM [PHOSPHOGYPSUM BM-3dg PLASTER OF PARIS NoGS 3-(TRIETHOXYSILYL)PROPYLAMINE LT-UNK | SKI CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE LT-UNK QUARTZ BM-1 | CAN PORTLAND CEMENT LT-P1 | CAN | END WOOD DUST, CELLULOSE LT-1 | CAN | RES IRON, ELEMENTAL LT-P1 | END]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... BM-1
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This HPD includes the product with its ready-to-paint finish. These are custom finished or field finished. Because it is impossible to anticipate the custom finish that is not included. This is project design-based and could include metal or particleboard. The % of the composition, should it exist, is 1-2%. Residuals and impurities are considered in accordance with the HPD Best Practice Guidance, 10.02.17, version 1 "The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, in terms of level, i.e., 100 ppm or 1000 ppm. Residuals and impurities present below the declared Inventory Threshold do not need to be reported on the HPD." This includes average data as declared in the common product database or in peer-reviewed scientific articles. For this product, no actual material has been tested therefore residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD, otherwise, if none are listed then no residuals or impurities are common in that substance above the threshold. Every effort has been made to report the substances in this product by the manufacturer to the listed threshold. This is a voluntary, self-reported effort. Any errors or omissions shall be considered human error and therefore reported to the manufacturer. The manufacturer shall not be liable for omissions.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method V1.1 (Section 01350/CHPS) - Classroom & Office scenario

CONSISTENCY WITH OTHER PROGRAMS

Third Party Verified?

☐ Yes

☒ No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2022-06-06

PUBLISHED DATE: 2022-06-06

EXPIRY DATE: 2025-06-06

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

FORMGLAS GFRG, MOLDED GLASS FIBER REINFORCED GYPSUM %: 100.0000

PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES CONSIDERED: Yes	MATERIAL TYPE: Polymeric Material
RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are considered in accordance with the HPD Best Practice Guidance, 10.02.17, version 1 "The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, in terms of level, i.e., 100 ppm or 1000 ppm. Residuals and impurities present below the declared Inventory Threshold do not need to be reported on the HPD." This includes average data as declared in the common product database or in peer-reviewed scientific articles. For this product, no actual material has been tested therefore residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD, otherwise, if none are listed then no residuals or impurities are common in that substance above the threshold.		
OTHER MATERIAL NOTES: Per Formglass, all materials are reported in their published material ingredient inventory, to 0.1%. The wood or steel as listed on the SDS is basic particleboard used for reinforcements and a small steel wire loop for hanging. Since the threshold is small and the manufacturer does not have one source only for these items, basic material composition from the Quartz database of common building materials was used for the additional information. The main ingredient of steel is 98% iron therefore the threshold is met. Likewise for particleboard, wood dust is the main ingredient. All binders or other manufacturer-specific information is below the threshold. The data quality is complete but fair for this addition.		

PHOSPHOGYPSUM ID: 13397-24-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-06 10:24:05		
%: 88.9110 - 93.9060	GS: BM-3dg	RC: UNK	NANO: No	SUBSTANCE ROLE: Filler
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: Gypsum : All impurities are at an unknown level. Per Pahros "In addition to the radiation health hazards covered by Subpart R, phosphogypsum contains some trace metals in concentrations that EPA believes may pose a chemical hazard to human health and the environment. Analysis of samples from various facilities contained arsenic, lead, cadmium, chromium, fluoride, zinc, antimony, and copper at concentrations that may pose significant health risks. The concentrations of these contaminants vary by more than three orders of magnitude among samples taken from various locations. These trace metals may also be leached from phosphogypsum and migrate to nearby surface and groundwater resources." (EPA phosphogypsum webpage)				

PLASTER OF PARIS ID: 26499-65-0

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-06 10:24:08		
%: 3.9960 - 5.9940	GS: NoGS	RC: UNK	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: Impurities were considered and are at an unknown level. Per Paros "To produce plasters or wallboard, gypsum must be partially dehydrated or calcined to produce calcium sulfate hemihydrate (CaSO4 ½H2O), commonly called stucco." (EPA)				

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-06 10:24:11		
%: 1.0000	GS: LT-UNK	RC: UNK	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS	
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1		H314 - Causes severe skin burns and eye damage [Skin corrosion/irritation - Category 1A or 1B or 1C]	

SUBSTANCE NOTES: This binder is included in the material ingredient inventory published by the manufacturer. Per a phone call with the manufacturer, the minimum percentage of composition was 1%. All additional percentages are considered trade secret information and were not disclosed.

Residuals and impurities are considered in accordance with the HPD Best Practice Guidance, 10.02.17, version 1

“The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, in terms of level, i.e., 100 ppm or 1000 ppm. Residuals and impurities present below the declared Inventory Threshold do not need to be reported on the HPD.”

This includes average data as declared in the common product database or in peer-reviewed scientific articles. For this product, no actual material has been tested therefore residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material.

The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD, otherwise, if none are listed then no residuals or impurities are common in that substance above the threshold.

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-06 10:24:13		
%: 0.9990 - 1.9980	GS: LT-UNK	RC: UNK	NANO: No	SUBSTANCE ROLE: Structure component
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS	
None found			No warnings found on HPD Priority Hazard Lists	

SUBSTANCE NOTES: No known impurities or residuals per the Phros database.

Residuals and impurities are considered in accordance with the HPD Best Practice Guidance, 10.02.17, version 1

“The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, in terms of level, i.e., 100 ppm or 1000 ppm. Residuals and impurities present below the declared Inventory Threshold do not need to be reported on the HPD.”

This includes average data as declared in the common product database or in peer-reviewed scientific articles. For this product, no actual material has been tested therefore residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material.

The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD, otherwise, if none are listed then no residuals or impurities are common in that substance above the threshold.

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-06 10:24:16		
%: 0.9990 - 2.9970	GS: BM-1	RC: UNK	NANO: No	SUBSTANCE ROLE: Filler

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CAN	IARC	Group 1 - Agent is Carcinogenic to humans
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]
CAN	GHS - New Zealand	Carcinogenicity category 1

SUBSTANCE NOTES: All impurities and residuals are below the reporting threshold. Per the Pharos database, aluminum oxide <0.8% and iron oxide <0.10%. Titanium dioxide is also listed at <0.1%Pharos notes: "Only a few elements can replace silicon in the quartz lattice (substitutional positions) or are small enough to occupy free spaces in the lattice (interstitial positions). In natural quartz crystals, the most common ones to replace Si are Al, Fe, Ge, and Ti, whereas Li, Na, Ca, Mg and Fe often occupy interstitial positions in the "c-channels"." [Mindat]

PORTLAND CEMENT

ID: **65997-15-1**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-06 10:24:20		
#: 0.9900 - 5.9950	GS: LT-P1	RC: UNK	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor		

SUBSTANCE NOTES: All residuals and impurities are below the threshold. Per the Pharos database, Aluminum oxide is an impurity at 5%. Aluminum Oxide = 5% mass fraction of Portland Cement (NIST MSDS)

TSCA Definition 2008: Portland cement is a mixture of chemical substances produced by burning or sintering at high temperatures (greater than 1200.degree.C (2192.degree.F)) raw materials which are predominantly calcium carbonate, aluminum oxide, silica, and iron oxide. The chemical substances which are manufactured are confined in a crystalline mass. This category includes all of the chemical substances specified below when they are intentionally manufactured in the production of Portland cement. The primary members of the category are Ca₂SiO₄ and Ca₃SiO₅. Other compounds listed below may also be included in combination with these primary substances.: CaAl₂O₄; CaAl₄O₇; CaAl₁₂O₁₉; Ca₃Al₂O₆; Ca₁₂Al₁₄O₃₃; CaO; Ca₂Fe₂O₅; Ca₂Al₂SiO₇; Ca₄Al₆SO₁₆; Ca₁₂Al₁₄Cl₂O₃₂; Ca₁₂Al₁₄F₂O₃₂; Ca₄Al₂Fe₂O₁₀; Ca₆Al₁₄Fe₂O₁₅ (National Library of Medicine Record)

WOOD DUST, CELLULOSE

ID: **9004-34-6**

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-06 11:44:51		
#: 0.1000 - 2.0000	GS: LT-1	RC: UNK	NANO: No	SUBSTANCE ROLE: Structure component

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CAN	CA EPA - Prop 65	Carcinogen
RES	AOEC - Asthmagens	Asthmagen (Rs) - sensitizer-induced
SUBSTANCE NOTES:		

IRON, ELEMENTAL

ID: 7439-89-6

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-06-06 10:24:23		
%: 0.0100 - 2.0000	GS: LT-P1	RC: UNK	NANO: No	SUBSTANCE ROLE: Structure component
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS	
END	TEDX - Potential Endocrine Disruptors		Potential Endocrine Disruptor	
SUBSTANCE NOTES: This is a small steel ring that may be present in some panels for hanging.				

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS		CDPH Standard Method V1.1 (Section 01350/CHPS) - Classroom & Office scenario	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2014-02-	EXPIRY DATE:	CERTIFIER OR LAB: UL
APPLICABLE FACILITIES: Not a facility level verification	26		
CERTIFICATE URL:			
CERTIFICATION AND COMPLIANCE NOTES: This CDPH was performed by the manufacturer of the material, Formglass. RPG owns the mold for the materials. It is test #17896-03 and meets the classroom and office scenarios. Actual data about the amount of emissions is not included in the report.			

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

This HPD includes the product with its ready-to-paint finish. These are custom finished or field finished. Because it is impossible to anticipate the custom finish that is not included.

Residuals and impurities are considered in accordance with the HPD Best Practice Guidance, 10.02.17, version 1

“The threshold applied to Residuals and Impurities (R/I) is the same as the threshold applied to intentionally added substances, in terms of level, i.e., 100 ppm or 1000 ppm. Residuals and impurities present below the declared Inventory Threshold do not need to be reported on the HPD.”

This includes average data as declared in the common product database or in peer-reviewed scientific articles. For this product, no actual material has been tested therefore residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material.

The main databases used for researching potential residuals and impurities are Pharos and PubChem (formerly toxnet). Any R/I above the threshold shall be listed on the HPD, otherwise, if none are listed then no residuals or impurities are common in that substance above the threshold.

Every effort has been made to report the substances in this product by the manufacturer to the listed threshold. This is a voluntary, self-reported effort. Any errors or omissions shall be considered human error and therefore reported to the manufacturer. The manufacturer shall not be liable for omissions.

MANUFACTURER INFORMATION

MANUFACTURER: RPG Acoustical Systems LLC
ADDRESS: 99 South Street
 Passaic New Jersey 07055, USA
WEBSITE: www.rpgacoustic.com

CONTACT NAME: Ken Fussner
TITLE: Executive VP of Sales & Marketing
PHONE: 973-916-1166 X4000
EMAIL: kfussner@rpgacoustic.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
BM-2 Benchmark 2 (use but search for safer substitutes)	
BM-1 Benchmark 1 (avoid - chemical of high concern)	
BM-U Benchmark Unspecified (due to insufficient data)	
LT-P1 List Translator Possible 1 (Possible Benchmark-1)	NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.