

HPD UNIQUE IDENTIFIER: 29128

CLASSIFICATION: 07 84 53 Building Perimeter Firestopping

PRODUCT DESCRIPTION: The SpecSeal® Quick Clip™ L-Bracket Perimeter Fire Barrier System is designed to accelerate the installation of curtain wall insulation for perimeter fire barrier systems. Each L-Bracket is fastened into the mullion with steel screws to support the curtain wall insulation. Self-locking fasteners secure the insulation panels in place. The L-Bracket has a receiving slot to lock an “L-shaped” stiffener channel in place without the need for mechanical attachment by screws. The insulation fasteners are faster to install than screws or weld pins and lock in by hand. The L-Brackets are designed to provide easy location for the Quick Clip™ Fasteners. Unlike traditional insulation hangers with impaling pins or spikes that face out, the Quick Clip™ fasteners push in, affording workers better safety.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities	<i>All Substances Above the Threshold Indicated Are:</i>
☐ Nested Materials Method	☐ 100 ppm	☒ Considered	Characterized ☐ Yes Ex/SC ☒ Yes ☐ No
☒ Basic Method	☒ 1,000 ppm	☐ Partially Considered	<i>% weight and role provided for all substances.</i>
Threshold Disclosed Per	☐ Per GHS SDS	☐ Not Considered	Screened ☐ Yes Ex/SC ☒ Yes ☐ No
☐ Material	☐ Other	Explanation(s) provided for Residuals/Impurities?	<i>All substances screened using Priority Hazard Lists with results disclosed.</i>
☒ Product		☒ Yes ☐ No	Identified ☐ Yes Ex/SC ☒ Yes ☐ No
			<i>All substances disclosed by Name (Specific or Generic) and Identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SPECSEAL® QUICK CLIP™ L-BRACKET PERIMETER FIRE BARRIER SYSTEM [STEEL NoGS]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... NoGS

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

None.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE *See Section 3 for additional listings.*

VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2022-07-08
☐ Yes	VERIFIER:	PUBLISHED DATE: 2022-07-08
☒ No	VERIFICATION #:	EXPIRY DATE: 2025-07-08

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- *Basic Inventory method with Product-level threshold.*
- *Nested Material Inventory method with Product-level threshold*
- *Nested Material Inventory method with individual Material-level thresholds*

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

SPECSEAL® QUICK CLIP™ L-BRACKET PERIMETER FIRE BARRIER SYSTEM

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: There are no residuals in this product.

OTHER PRODUCT NOTES: There are no residuals in this product.

STEEL

ID: 12597-69-2

HAZARD SCREENING METHOD: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: 2022-07-08 11:26:01

%: 100.0000 - 100.0000

GS: NoGS

RC: None

NANO: No

SUBSTANCE ROLE: **Hardware**

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

None found

No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES: Heat treated galvanized steel.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	N/A
CERTIFYING PARTY: Self-declared	ISSUE DATE: 2019-03-12
APPLICABLE FACILITIES: All.	EXPIRY DATE:
CERTIFICATE URL:	CERTIFIER OR LAB: Self-declared.
CERTIFICATION AND COMPLIANCE NOTES: Not applicable. Not a wet applied product or type of insulation. See SDS under Certificate URL.	

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

The system's unique L-Bracket design allows for preinsulation of Curtain Wall Spandrel Panels on the factory floor or field installation of curtain wall insulation from the outside of the building. Mullion insulation applied below the floor is secured in place with spiral screws. SpecSeal® Quick Clip™ Perimeter Fire Barrier Systems are used in conjunction with UL Certified mineral wool and SpecSeal® brand coatings.

Performance

- Tested per ASTM E2307 for fire resistance
- Tested for wind cycling exposure in accordance with ASTM E1233
- Loading Equivalent to 108 mph wind for 500 cycles

Features & Benefits

- Quick installation
- Easy installation of stiffener channel
- Increased safety by reducing cutting sharp metal and impaling pins or spikes
- Patent pending design
- Allows for factory insulating of curtain wall spandrel panels

MANUFACTURER INFORMATION

MANUFACTURER: Specified Technologies Inc.
ADDRESS: 210 Evans Way
Somerville NJ 08876, United States
WEBSITE: www.stifirestop.com

CONTACT NAME: George Gornick
TITLE: George Gornick, LEED Green Associate
PHONE: 800-992-1180, Ext. 1013
EMAIL: ggornick@stifirestop.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

LAN Land toxicity

MAM Mammalian/systemic/organ toxicity

MUL Multiple

NEU Neurotoxicity

NF Not found on Priority Hazard Lists

OZO Ozone depletion

PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or reactive)

REP Reproductive

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (due to insufficient data)

LT-P1 List Translator Possible 1 (Possible Benchmark-1)

LT-1 List Translator 1 (Likely Benchmark-1)

LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)

NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content

PostC Post-consumer recycled content

UNK Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material

Nested Method / Product Threshold Substances listed within each material per threshold indicated per product

Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.