

HPD UNIQUE IDENTIFIER: 38766828544

HPD UNIQUE PRODUCT ID: Not provided.

CLASSIFICATION: 07 84 53 Building Perimeter Firestopping

PRODUCT DESCRIPTION: SpeedFlex® Track Top Gasket (TTG) is a patented thin profile intumescent cover for gypsum wall framing for tracks, runners and studs that is designed to provide fire, smoke and acoustical ratings for head of wall joints, wall to wall joints, bottom of wall joints and perimeter fire-barrier between gypsum wall(s) and concrete. TTG is compatible with most ceiling track and provides an economical method of providing the required seal in rated and non-rated wall construction. Installed on the track prior to installation, the wall is effectively sealed against fire, smoke, and sound transmission during the construction process, thereby providing cost savings. TTG allows up to 100% movement. The red color is easy to identify and easy to inspect, and it is not susceptible to cracking, sagging, or dripping. Applications: Head-of-Wall, Bottom-of-Wall, Wall-to-Wall Joints or Perimeter Fire-Barrier. Gypsum to Flat Concrete Slab Non-rated acoustical wall(s) or fire/smoke rated wall(s). Specifications: Systems may allow for up to 100-percent compression and/or extension from the joint's installed width. Systems meet cyclic movement criteria for thermal (Class I), windsway (Class II) and seismic (Class III). The approved system materials shall be UL Classified. Performance: Fire Standards - ASTM E1966, ANSI/UL2079, CAN/ULC S115, ASTM E2307. For 1 and 2 hour assembly ratings. Acoustical Standards - ASTM E 90-09, ASTM C919. For Up to 56 STC (Relates to specific construction). Air/Smoke Leakage - ANSI/UL2079. For <1 CFM/Lin Ft

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY		
Inventory Reporting Format	Residuals/Impurities Evaluation	For all contents above the threshold, the manufacturer has:
→ Basic Method	→ Completed	
Threshold Disclosed Per	Explanation(s) provided :	
→ Product	Yes	
Threshold Level		
→ 1,000 ppm		
	Characterized	Yes
	Provided weight and role.	
	Screened	Yes
	Provided screening results using HPDC-approved methods.	
	Identified	No
	Provided name and CAS RN or other identifier.	

CONTENT IN DESCENDING ORDER OF QUANTITY	
Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.	Number of Greenscreen BM-4/BM3 contents ... 0
	Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... None
	Nanomaterial ... No
PRODUCT MATERIAL OR SUBSTANCE RESIDUAL OR IMPURITY	INVENTORY AND SCREENING NOTES:
GREENSCREEN SCORE HAZARD TYPE	None.
SPEEDFLEX® TRACK TOP GASKET (TTG) [GRAPHITE LT-UNK] CAN	
UNDISCLOSED NoGS POLYETHYLENE LT-UNK 2-PROPENOIC ACID, 2-METHYL-, POLYMER WITH BUTYL 2-PROPENOATE, ETHENYLBENZENE, 2-ETHYLHEXYL 2-PROPENOATE AND METHYL 2-METHYL-2-PROPENOATE NoGS UNDISCLOSED LT-UNK	

VOLATILE ORGANIC COMPOUND (VOC) CONTENT	COMPLIANCE See Section 3 for additional listings.
VOC Content data is not applicable for this product category.	VOC emissions: N/A
	CONSISTENCY WITH OTHER PROGRAMS
	No pre-checks completed or disclosed.

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 3.0, available on the HPDC website at: www.hpd-collaborative.org/hpd-3-0-standard

SPEEDFLEX® TRACK TOP GASKET (TTG)

PRODUCT THRESHOLD: 1000 ppm RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: There are no residuals in this material.

OTHER PRODUCT NOTES: There are no residuals in this material.

GRAPHITE

ID: 7782-42-5

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:24:12	
%: 25.0000 - 40.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Intumescent
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is the intumescent in the product.				

UNDISCLOSED

ID: Undisclosed

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:24:12	
%: 30.0000 - 40.0000	GreenScreen: NoGS	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions		
		Exempted from REACH Annex IV listing due to intrinsic safety		
SUBSTANCE NOTES: This is part of the binder in the product.				

POLYETHYLENE				ID: 9002-88-4	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:24:12		
%: 25.0000 - 35.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Structure component	
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
None found			No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION		
None found			No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is the HDPE backing on the product.					

2-PROPENOIC ACID, 2-METHYL-, POLYMER WITH BUTYL 2-PROPENOATE, ETHENYLBENZENE, 2-ETHYLHEXYL 2-PROPENOATE AND METHYL 2-METHYL-2-PROPENOATE				ID: Undisclosed
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:24:13	
%: 5.0000 - 10.0000	GreenScreen: NoGS	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
None found			No warnings found on HPD Priority Hazard Lists	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	
SUBSTANCE NOTES: This is part of the binder in the product.				

UNDISCLOSED			ID: Undisclosed	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-04-14 8:24:13	
%: 0.5000 - 2.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Carrier
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is a carrier in the product.				

Section 3: Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	N/A	
COMPLIANCE TYPE: Self-declared	ISSUE	EXPIRY
CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: Self-declared.	DATE:	DATE: No
COMPLIANCE DETAILS:	2017-01-	expiration
COMPLIANCE SCOPE:	24	
APPLICABLE FACILITIES: All.		
COMPLIANCE URL:		
https://files.stifirestop.com/5.%20Safety%20Data%20Sheets/1.%20English/SDS_SpeedFlex%20Track%20Top%20Gasket.pdf		
COMPLIANCE NOTES: Not Applicable. SDS attached (Certificate URL).		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Maintenance:

Installations should be inspected periodically for subsequent damage. Any damage should be repaired using SpecSeal® Firestop Products per the original approved design.

Features & Benefits:

- Easy to install; easy to inspect.
- Easy to cut; use scissors or a sharp knife.
- No waste; use as needed.
- Works with most ceiling tracks.
- Firestop as the wall is constructed.
- Water resistant.
- Won't crack, sag, or drip; done right the first time, and no costly callbacks.
- Cost savings; no secondary trips up the ladder or caulking crews on scissor lifts.
- Red for easy identification with UL Mark prominently displayed to satisfy inspectors and AHJ's.
- Acoustical values (STC) in both rated and non-rated construction allowing you to use one product for the entire job.
- L Ratings per UL2079 for use in smoke barrier construction.

MANUFACTURER INFORMATION

MANUFACTURER: **Specified Technologies Inc.**
ADDRESS: **210 Evans Way**
Somerville, NJ 08876
COUNTRY: **USA**

WEBSITE: **www.stifirestop.com**
CONTACT NAME: **George Gornick, LEED Green Associate**
TITLE: **Applications Engineer**
PHONE: **800-992-1180 Ext. 1013**
EMAIL: **ggornick@stifirestop.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold	Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold	Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold	Substances listed individually per threshold indicated per product

Nano	Composed of nano scale particles or nanotechnology
Third Party Verified	Verification by independent certifier approved by HPDC
Preparer	Third party preparer, if not self-prepared by manufacturer
Applicable facilities	Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.