

SpecSeal® Ready® Sleeve Firestop Sleeve
by Specified Technologies Inc.

SCREENING DATE: 2025-11-21
PUBLISHED DATE: 2025-11-21
EXPIRY DATE: 2028-11-21
PREPARER: Self-Prepared

Health Product
Declaration v3.0

created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 57784647680
HPD UNIQUE PRODUCT ID: Not provided.
CLASSIFICATION: 07 84 13.16 Penetration Firestopping Devices

PRODUCT DESCRIPTION: SpecSeal® Ready® Sleeve Pathways are a complete UL® Certified out-of-the-box solution for new cable penetrations through walls. Each sleeve kit contains a precut metallic sleeve, mounting escutcheons, intumescent escutcheon gaskets, wall labels, and the amount of putty required to seal both ends. SpecSeal® Ready® Sleeve Pathway kits are simple in design and installation. All sizes of the Sleeve Pathways include a unique pressfit end cap design to eliminate potential sharp edges and do away with the need for conduit bushings. SpecSeal® Ready® Sleeve Pathways are sized to the same O.D. as standard EMT (Electrical Mechanical Tubing) and will accept EMT accessories such as grounding bushings. Additionally, SpecSeal® Ready® Sleeve Pathways provide an easy method for compliance with the sleeve attachment requirements of the 2015 IBC Section 714.2 and 2018 IBC Section 714.3 without the need for struts or other bracing. Applications SpecSeal® Ready® Sleeve Pathways are used to protect or support cables in both non-rated and rated construction. SpecSeal® Ready® Sleeve Pathways are suitable for use in all common constructions including concrete floors, concrete walls, concrete block walls, and gypsum board/stud wall assemblies up to 10" (254 mm) thick.

Section 1: SummaryBasic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Residuals/Impurities Evaluation	For all contents above the threshold, the manufacturer has:
→ Basic Method	→ Completed	
Threshold Disclosed Per	Explanation(s) provided :	Characterized
→ Product	Yes	Provided weight and role.
Threshold Level		Screened
→ 1,000 ppm		Provided screening results using HPDC-approved methods.
		Identified
		Provided name and CAS RN or other identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE

SPECSEAL® READY® SLEEVE FIRESTOP SLEEVE [STEEL NoGS
GRAPHITE LT-UNKALUMINA TRIHYDRATE BM-2 | SKI | EYE
UNDISCLOSED LT-UNKCELLULOSE PULP NoGSUNDISCLOSED LT-
UNKUNDISCLOSED NoGSUNDISCLOSED LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0
Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ...
None
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

None.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

COMPLIANCE See Section 3 for additional listings.
VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 3.0, available on the HPDC website at: www.hpd-collaborative.org/hpd-3-0-standard

SPECSEAL® READY® SLEEVE FIRESTOP SLEEVE

PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes
RESIDUALS AND IMPURITIES NOTES: There are no residuals in this product.	
OTHER PRODUCT NOTES: There are no residuals in this product.	

STEEL				ID: 12597-69-2	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-21 14:41:12		
%: 75.0000 - 85.0000	GreenScreen: NoGS	RC: None	NANO: No	SUBSTANCE ROLE: Structure component	
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
None found			No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION		
None found			No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is the zinc-plated steel sleeve and escutcheon plate assembly.					

GRAPHITE				ID: 7782-42-5
HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2025-11-21 14:41:13		
%: 2.0000 - 7.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Intumescent
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is the intumescent contained in the sleeve gasket and firestop putty dosage.				

ALUMINA TRIHYDRATE				ID: 21645-51-2
--------------------	--	--	--	----------------

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-21 14:41:13	
?: 2.0000 - 7.0000	GreenScreen: BM-2	RC: None	NANO: No	SUBSTANCE ROLE: Flame retardant
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
SKI	GHS - New Zealand		Skin irritation category 2	
EYE	GHS - New Zealand		Eye irritation category 2	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CP II)		C2C Certified v4.1 Product Standard Restricted Substances - Effective July 1, 2025	
			Children's Toy Products	
SUBSTANCE NOTES: This is a flame retardant in the firestop putty dosage.				

UNDISCLOSED			ID: Undisclosed	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-21 14:41:14	
?: 1.0000 - 5.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is the part of the binder system for the firestop putty dosage.				

CELLULOSE PULP				ID: 65996-61-4
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-21 14:41:14	
?: 1.0000 - 4.0000	GreenScreen: NoGS	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
None found			No warnings found on HPD Priority Hazard Lists	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
EXEMPT	European Union / European Commission (EU EC)		EU - REACH Exemptions	
			Exempted from REACH Annex IV listing due to intrinsic safety	
SUBSTANCE NOTES: This is part of the binder system in the sleeve gasket.				

UNDISCLOSED			ID: Undisclosed	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-21 14:41:13	
%: 0.5000 - 3.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is part of the binder system for the firestop putty dosage.				

UNDISCLOSED			ID: Undisclosed	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-21 14:41:13	
%: 0.5000 - 1.5000	GreenScreen: NoGS	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is part of the binder system in the intumescent gasket.				

UNDISCLOSED			ID: Undisclosed	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2025-11-21 14:41:14	
%: 0.1000 - 1.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This is part of the binder system for the intumescent gasket.				

Section 3: Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	N/A	
COMPLIANCE TYPE: Self-declared	ISSUE DATE: 2017-07-12	EXPIRY DATE: No expiration
CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: Self-declared.		
COMPLIANCE DETAILS:		
COMPLIANCE SCOPE:		
APPLICABLE FACILITIES: All.		
COMPLIANCE URL:		
https://files.stifirestop.com/5.%20Safety%20Data%20Sheets/1.%20English/SDS_Ready%20Sleeve.pdf		
COMPLIANCE NOTES: Not applicable. Not a wet applied product or type of insulation. See SDS under Certificate URL.		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Specifications

All data, video, communication, power, and control cables shall be installed through sleeves wherever said cables penetrate fire resistance rated barriers. The sleeve shall be sized to accommodate the present cable bundle as well as anticipated growth. The sleeve kit shall include steel escutcheon plates and intumescent firestop gaskets sized to fit the specific outside diameter of the sleeve and sandwich the barrier to lock said sleeve in place. The sleeve shall be provided with a sufficient thickness of intumescent firestop putty to seal the ends of the sleeve to restrict the passage of fire, smoke, and superheated gases. The firestop sleeve shall be UL Certified and tested to the requirements of ASTM E 814 (ANSI/UL1479) and CAN/ULC- S115.

Specified Divisions

Division 7 07 84 13 Penetration Firestopping

Division 23 23 00 00 HVAC

Division 26 26 00 00 Electrical

Performance

SpecSeal® Ready® Sleeve pathways are UL tested and Certified in accordance with ASTM E814 (UL1479) and CAN/ULC- S115. Systems are available for cable penetrations through common wall constructions up to and including 4 hours.

Features & Benefits

- Economical: Offers significant material and labor savings.
- Ready to Install: No cutting required, no waste!
- Locks Into Place: No support struts and clamps required
- No External Firestop Seal Required: Factory supplied intumescent firestop gasket
- Firestop Putty Provided with Kit: Sufficient to seal ends to 1" (25 mm) depth
- UL Classified and Code Compliant
- For Rated and Non-Rated Barriers: Putty seal impedes the passage of fire, smoke, superheated gases, particulate dust, and minimizes noise transmission

MANUFACTURER INFORMATION

MANUFACTURER: **Specified Technologies Inc.**
ADDRESS: **210 Evans Way**
Somerville, NJ 08876
COUNTRY: **United States**

WEBSITE: **www.stifirestop.com**
CONTACT NAME: **George Gornick, LEED Green Associate**
TITLE: **Applications Engineer**
PHONE: **800-992-1180, Ext. 1013**
EMAIL: **ggornick@stifirestop.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.