

HPD UNIQUE IDENTIFIER: 29136

CLASSIFICATION: 07 84 00 Firestopping

PRODUCT DESCRIPTION: SpecSeal® SpeedFlex® Joint Profile is a high temperature fibrous joint forming material for use in top of wall construction joints. When installed with an approved SpecSeal® firestop coating, the profile allows for economical installations and up to 100-percent compression and extension in joint movement. Applications SpecSeal® SpeedFlex® Joint Profile replaces strips of mineral wool forming material in the joint area between the fire-rated wall assembly and the bottom of a steel deck or concrete floor. SpecSeal® SpeedFlex® Joint Profiles are tacked in place with staples and coated with an approved SpecSeal® firestop coating applied to a 1/8" (3.2mm) wet thickness. The shape of the product allows for 100-percent compression and extension in joint movement for Class 1 (500 cycles at 1 cycle per minute (cpm)), Class II (500 cycles at 10 cpm) and Class III (100 cycles at 30 cpm) joint applications as required by the applicable building code.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format ☐ Nested Materials Method ☒ Basic Method	Threshold Level ☐ 100 ppm ☒ 1,000 ppm ☐ Per GHS SDS ☐ Other	Residuals/Impurities ☒ Considered ☐ Partially Considered ☐ Not Considered Explanation(s) provided for Residuals/Impurities? ☒ Yes ☐ No	<i>All Substances Above the Threshold Indicated Are:</i> Characterized ☐ Yes Ex/SC ☒ Yes ☐ No <i>% weight and role provided for all substances.</i> Screened ☐ Yes Ex/SC ☒ Yes ☐ No <i>All substances screened using Priority Hazard Lists with results disclosed.</i> Identified ☐ Yes Ex/SC ☐ Yes ☒ No <i>One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.</i>
---	---	---	--

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE
SPECSEAL® SPEEDFLEX® JOINT PROFILE [CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE LT-UNK UNDISCLOSED LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-UNK

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

None.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1

Third Party Verified? ☐ Yes ☒ No	PREPARER: Self-Prepared VERIFIER: VERIFICATION #:	SCREENING DATE: 2022-07-08 PUBLISHED DATE: 2022-07-08 EXPIRY DATE: 2025-07-08
--	--	--

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

SPECSEAL® SPEEDFLEX® JOINT PROFILE

PRODUCT THRESHOLD: 1000 ppm		RESIDUALS AND IMPURITIES CONSIDERED: Yes		
RESIDUALS AND IMPURITIES NOTES: This product may contain trace residual formaldehyde (<0.1%)				
OTHER PRODUCT NOTES: This product may contain trace residual formaldehyde (<0.1%)				
CONTINUOUS FILAMENT GLASS FIBER, NON-RESPIRABLE				ID: 65997-17-3
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-07-08 11:56:13		
%: 80.0000 - 85.0000	GS: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Filler
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: This is the filler in the product.				

UNDISCLOSED				ID: Undisclosed
HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2022-07-08 11:56:13		
%: 15.0000 - 20.0000	GS: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
SUBSTANCE NOTES: This is the cured binder in the product.				

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	N/A		
CERTIFYING PARTY: Self-declared	ISSUE	EXPIRY	CERTIFIER
APPLICABLE FACILITIES: All.	DATE:	DATE:	OR LAB:
CERTIFICATE URL:	2017-		Self-
https://files.stifirestop.com/5.%20Safety%20Data%20Sheets/1.%20English/SDS_SpeedFlex%20Joint%20Profile.pdf	07-13		declared.
CERTIFICATION AND COMPLIANCE NOTES: Not applicable. Not a wet applied product or type of insulation. See SDS under Certificate URL.			

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Specifications

All head-of-wall conditions shall be sealed with water-based wet film coatings. The system, as installed, shall allow for up to 100-percent compression and/ or extension from the joint's installed width. Systems comprised of sealant and forming materials shall meet cyclic movement criteria for thermal (Class I), windsway (Class II) and seismic (Class III). The approved system materials shall be UL Certified.

Specified Divisions

Division 7 07 84 00 General Firestopping

Division 7 07 84 43 Fire Resistive Joint Systems

Division 9 09 20 00 Plaster and Gypsum Board

Performance

When installed in conjunction with an approved SpecSeal® Firestop Coating, SpecSeal® SpeedFlex® Joint Profiles have been successfully tested in one and two hour joints to the exacting criteria of ANSI/UL 2079 (ASTM E 1966) and CAN/ULC-S115. All tested systems meet Class I, Class II and Class III movement criteria. Consult factory for individual system designs and application requirements. **LIMITATIONS:** Use product as per manufacturer's instructions. Use only in applications per the manufacturer's tested and published designs or per specific recommendations. End user must determine the suitability of the product and designs to his or her specific requirement and assumes responsibility for use of product.

Features & Benefits

- Allows 100% compression or extension
- Fast Installation
- Alternative to caulking joints

MANUFACTURER INFORMATION

MANUFACTURER: Specified Technologies Inc.
ADDRESS: 210 Evans Way
 Somerville NJ 08876, United States
WEBSITE: www.stifirestop.com

CONTACT NAME: George Gornick, LEED Green Associate
TITLE: Applications Engineer
PHONE: 800-992-1180, Ext. 1013
EMAIL: ggornick@stifirestop.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY
Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)
BM-2 Benchmark 2 (use but search for safer substitutes)	
BM-1 Benchmark 1 (avoid - chemical of high concern)	
BM-U Benchmark Unspecified (due to insufficient data)	
LT-P1 List Translator Possible 1 (Possible Benchmark-1)	NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.