

HPD UNIQUE IDENTIFIER: 1134497498112

CLASSIFICATION: 09 83 13 Acoustic Wall Coating

PRODUCT DESCRIPTION: Vetotop UC371 is a two-component, solvent-based polyurethane topcoat. It is used as UV resistant sealer over concrete and a range of Vetotop epoxy and polyurethane flooring & coating systems. Special additives and adhesion promoters give this material excellent penetration and adhesion to minimally profiled concrete. Vetotop UC371 is UV stable for exterior applications, cures rapidly, and the sealed system is ideal for all-weather exposure. Vetotop UC371 gives a hard, glossy surface that offers excellent scratch resistance and easy cleanability when used as a finish coat. Vetotop UC371 is supplied in a pack size of 4 liters kit consisting of Resin & Hardener.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	For all contents above the threshold, the manufacturer has:
☒ Nested Materials Method	☐ 100 ppm	☐ Completed	Characterized ☒ Yes ☐ No
☐ Basic Method	☒ 1,000 ppm	☒ Not Completed	Provided weight and role.
Threshold Disclosed Per	☐ Per GHS SDS	Explanation(s) provided for Residuals/Impurities?	Screened ☒ Yes ☐ No
☐ Material	☐ Other	☒ Yes ☐ No	Provided screening results using HPDC-approved methods.
☒ Product			Identified ☒ Yes ☐ No
			Provided name and CAS RN or other identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

VETOTOP UC371 [POLYESTER FIBERS NoGS BARIUM SULFATE BM-2 | CAN | MAM METHOXYISOPROPYL ACETATE LT-UNK | EYE XYLENES BM-1 | END | MUL | REP | SKI | EYE | MAM | AQU METHYL ETHYL KETONE LT-P1 | END | EYE | PHY | MAM | SKI]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... BM-1, LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.3 and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product, along with the role and percent weight. Therefore, this HPD is consistent with the LEED v4.1 MR Credit Building Product Disclosure and Optimization: Material Ingredient Reporting (Option 1).

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 244 Regulatory (g/l): 450

Does the product contain exempt VOCs: No

Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario

VOC content: ANSI/BIFMA M7.1 Standard Test Method for Determining VOC Emissions - X7.1-2011 FES Test method

LCA: Environmental Product Declaration (EPD) by the Green Standard

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4.1 Option 1.

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2023-03-23
☐ Yes	VERIFIER:	PUBLISHED DATE: 2023-05-28
☒ No	VERIFICATION #:	EXPIRY DATE: 2026-03-23

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

VETOTOP UC371

%: 100.0000

PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No	MATERIAL TYPE: Other: HIGH PERFORMANCE, CHEMICAL SCRATCH & UV RESISTANT POLYESTER POLYURETHANE FLOOR & WALL COATING
RESIDUALS AND IMPURITIES NOTES: No residuals or impurities are considered		
OTHER MATERIAL NOTES: All substances in this material are below the reportable threshold.		

POLYESTER FIBERS

ID: 80595-68-2

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-03-23 2:09:23		
%: 25.0000 - 40.0000	GreenScreen: NoGS	RC: None	NANO: No	SUBSTANCE ROLE: Structure component
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES:				

BARIUM SULFATE

ID: 7727-43-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-03-23 2:11:50		
%: 25.0000 - 40.0000	GreenScreen: BM-2	RC: None	NANO: No	SUBSTANCE ROLE: Pigment
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CP II)	C2C Certified v4 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022
		Biological and Environmentally Released Materials
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CP II)	C2C Certified v4 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022
		Children's Products
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CP II)	C2C Certified v4 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022
		Cosmetics & Personal Care Products
SUBSTANCE NOTES:		

XYLENES					ID: 1330-20-7
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2023-03-23 2:09:51		
%: 3.0000 - 6.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Structure component	

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
REP	GHS - Japan	H360 - May damage fertility or the unborn child [Toxic to reproduction - Category 1B]
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
SKI	GHS - New Zealand	Skin irritation category 2
EYE	GHS - New Zealand	Eye irritation category 2
SKI	GHS - Australia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Japan	H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]
SKI	GHS - Japan	H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]
REP	GHS - New Zealand	Reproductive toxicity category 2
EYE	GHS - Korea	H319 - Causes serious eye irritation [Serious eye damage/irritation - Category 2]
SKI	GHS - Korea	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
MAM	GHS - Korea	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - Repeated exposure - Category 1]
AQU	GHS - Japan	H401 - Toxic to aquatic life [Hazardous to the aquatic environment (acute) - Category 2]
AQU	GHS - Japan	H411 - Toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 2]
SKI	GHS - Malaysia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes of Problematic Chemicals Antimicrobials
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes of Problematic Chemicals Some Solvents
SUBSTANCE NOTES:		

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-03-23 2:11:06		
%: 1.0000 - 2.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Structure component
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor		
EYE	EU - GHS (H-Statements) Annex 6 Table 3-1	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]		
PHY	EU - GHS (H-Statements) Annex 6 Table 3-1	H225 - Highly flammable liquid and vapour [Flammable liquids - Category 2]		
EYE	GHS - New Zealand	Eye irritation category 2		
EYE	GHS - Australia	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
SKI	GHS - Japan	H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]		
MAM	GHS - Japan	H371 - May cause damage to organs [Specific target organs/systemic toxicity following single exposure - Category 2]		
EYE	GHS - Korea	H319 - Causes serious eye irritation [Serious eye damage/irritation - Category 2]		
PHY	GHS - Korea	H225 - Highly flammable liquid and vapour [Flammable liquids - Category 2]		
PHY	GHS - New Zealand	Flammable liquids category 2		
PHY	GHS - Japan	H225 - Highly flammable liquid and vapour [Flammable liquids - Category 2]		
PHY	GHS - Malaysia	H225 - Highly flammable liquid and vapour [Flammable liquids - Category 2]		
PHY	GHS - Australia	H225 - Highly flammable liquid and vapour [Flammable liquids - Category 2]		
EYE	GHS - Japan	H319 - Causes serious eye irritation [Serious eye damage / eye irritation - Category 2A]		
EYE	GHS - Malaysia	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes of Problematic Chemicals		
		Some Solvents		
SUBSTANCE NOTES:				

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2020-01-22	CERTIFIER OR LAB: Advanced
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE:	Laboratory Center LLC
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Volatile Organic Compound (VOC) - 244 g/L		
VOC CONTENT	ANSI/BIFMA M7.1 Standard Test Method for Determining VOC Emissions - X7.1-2011 FES Test method	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2020-01-22	CERTIFIER OR LAB: Advanced
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE:	Laboratory Center LLC
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: VOC Content - 244 g/l USEPA Method 24		
LCA	Environmental Product Declaration (EPD) by the Green Standard	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2023-05-30	CERTIFIER OR LAB: Environmental
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE: 2028-05-30	Footprint Institute
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Environmental Product Declaration has been developed by GCAS Quality Certifications and verified by a third-party verifier in Environmental Footprint Institute, Spain.		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

The original sealed kit of Vetotop UC371 has a shelf life of 12 months, provided it is stored clear of ground in a dry and shaded place below 35°C. Vetotop UC371 is irritant and harmful; therefore, avoid direct contact with the eyes or skin. It is recommended to use protective gloves and goggles during application. In case of contact with eyes, clean immediately with plenty of clean cold water and seek medical advice. Ensure adequate ventilation when using the product or when using solvent for cleaning purposes and avoid vapors' inhalation. The use of barrier creams provides additional skin protection. In case of skin contact, rinse with plenty of clean water, and cleanse with soap and water. Do not use solvent. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice. If swallowed, seek medical attention immediately - Do not induce vomiting. Vetotop UC371 is flammable. Keep away from sources of ignition. No Smoking. In the event of a fire, extinguish it with CO2 or foam.

MANUFACTURER INFORMATION

MANUFACTURER: Saudi Vetonit Co.Ltd
ADDRESS: P.O. Box 52235
 Riyadh - 11563, Saudi Arabia
WEBSITE: www.saveto.com

CONTACT NAME: Mr. Majid R Al Momani
TITLE: Research & Development Manager
PHONE: +966 11 265 3334
EMAIL: mmomani@saveto.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.