

HPD UNIQUE IDENTIFIER: 448103017472

CLASSIFICATION: 07 13 53 Elastomeric Sheet Waterproofing

PRODUCT DESCRIPTION: Vetoproof UM766 is a premium quality pitch extended polyurethane waterproofing membrane; the product is a liquid applied that hardens through reaction with atmospheric water vapor to form a highly elastic rubbery jointless membrane that is resistant to aggressive groundwater and sewage. Vetoproof UM766 can be applied at 0.7mm on vertical application.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	For all contents above the threshold, the manufacturer has:
☒ Nested Materials Method	☐ 100 ppm	☐ Completed	Characterized ☒ Yes ☐ No
☐ Basic Method	☒ 1,000 ppm	☒ Not Completed	Provided weight and role.
Threshold Disclosed Per	☐ Per GHS SDS	Explanation(s) provided for Residuals/Impurities?	Screened ☒ Yes ☐ No
☐ Material	☐ Other	☒ Yes ☐ No	Provided screening results using HPDC-approved methods.
☒ Product			Identified ☐ Yes ☒ No
			Provided name and CAS RN or other identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

VETOPROOF UM766 [QUARTZ BM-1*] CAN | MAM | GEN

POLYCAPROLACTONE, DIPROPYLENE GLYCOL, METHYLENEBIS(PHENYL ISOCYANATE) POLYMER NoGS ASPHALT LT-1 | CAN | MAM | GEN STODDARD SOLVENT LT-1 | CAN | MUL | GEN | MAM | SKI | AQU TECHNICAL/OTHER NAMES THAT MATCH YOUR QUERY: NoGS]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.3 and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product, along with the role and percent weight. Therefore, this HPD is consistent with the LEED v4.1 MR Credit Building Product Disclosure and Optimization: Material Ingredient Reporting (Option 1).

*Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. For this reason, this score is intentionally omitted from the "Contents highest concern" line above. See HPDC's Special Conditions policy for more information.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 9.6 Regulatory (g/l): 450

Does the product contain exempt VOCs: No

Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario

VOC content: ANSI/BIFMA M7.1 Standard Test Method for Determining VOC Emissions - X7.1-2011 FES Test method

LCA: Environmental Product Declaration (EPD) by the Green Standard

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4.1 Option 1.

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

VETOPROOF UM766

%: 100.0000

PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No	MATERIAL TYPE: Other: ELASTOMERIC POLYURETHANE LIQUID APPLIED WATERPROOFING MEMBRANE
RESIDUALS AND IMPURITIES NOTES: No residuals or impurities are considered		
OTHER MATERIAL NOTES: All substances in this material are below the reportable threshold.		

QUARTZ

ID: 14808-60-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-03-22 13:45:03		
%: 25.0000 - 40.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Filler

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen**
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route**
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)**
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man**
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources**
CAN	IARC	Group 1 - Agent is Carcinogenic to humans**
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen**
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]**
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]**
CAN	GHS - New Zealand	Carcinogenicity category 1**
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]**
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]**
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1**
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Silica sand (quartz) is a naturally washed sand that comes from nature without any further processing, only segregated to the desired sizes by sieving units and it does not contain inhalable particles (minimum), usually, the contact with humans mainly when it is in its wet form where no dust at all, in fact, it is safe.

**Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.

POLYCAPROLACTONE, DIPROPYLENE GLYCOL, METHYLENEBIS(PHENYL ISOCYANATE) POLYMER
ID: 154336-14-8

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-03-22 13:46:08		
%: 20.0000 - 35.0000	GreenScreen: NoGS	RC: None	NANO: No	SUBSTANCE ROLE: Polymer species
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
None found		No warnings found on HPD Priority Hazard Lists		

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES:				

ASPHALT

ID: 8052-42-4

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-03-22 13:44:15		
%: 15.0000 - 25.0000	GreenScreen: LT-1	RC: None	NANO: No	SUBSTANCE ROLE: Structure component
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen		
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
CAN	IARC	Group 2b - Possibly carcinogenic to humans		
CAN	GHS - Japan	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES:				

STODDARD SOLVENT

ID: 8052-41-3

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-03-22 13:45:37		
%: 5.0000 - 10.0000	GreenScreen: LT-1	RC: None	NANO: No	SUBSTANCE ROLE: Solvent

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	EU - REACH Annex XVII CMRs	Carcinogen Category 2 - Substances which should be regarded as if they are Carcinogenic to man
CAN	EU - Annex VI CMRs	Carcinogen Category 1B - Presumed Carcinogen based on animal evidence
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
GEN	EU - REACH Annex XVII CMRs	Mutagen Category 2 - Substances which should be regarded as if they are Mutagenic to man
GEN	EU - Annex VI CMRs	Mutagen - Category 1B
CAN	GHS - Australia	H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]
GEN	GHS - Australia	H340 - May cause genetic defects [Germ cell mutagenicity - Category 1A or 1B]
CAN	GHS - Malaysia	H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]
GEN	GHS - Malaysia	H340 - May cause genetic defects [Germ cell mutagenicity - Category 1A or 1B]
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1	H350 - May cause cancer [Carcinogenicity - Category 1A or 1B]
MAM	EU - GHS (H-Statements) Annex 6 Table 3-1	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]
MAM	EU - GHS (H-Statements) Annex 6 Table 3-1	H304 - May be fatal if swallowed and enters airways [Aspiration hazard - Category 1]
GEN	EU - GHS (H-Statements) Annex 6 Table 3-1	H340 - May cause genetic defects [Germ cell mutagenicity - Category 1A or 1B]
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]
SKI	GHS - Japan	H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]
AQU	GHS - Japan	H400 - Very toxic to aquatic life [Hazardous to the aquatic environment (acute) - Category 1]
AQU	GHS - Japan	H410 - Very toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 1]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes of Problematic Chemicals Some Solvents
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CP II)	C2C Certified v4 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022 Formulated Consumer Products
SUBSTANCE NOTES:		

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2023-03-22 13:46:31

%: 1.0000

GreenScreen: NoGS

RC: None

NANO: No

SUBSTANCE ROLE: Tensile strength additive

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES:

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2023-05-11	CERTIFIER OR LAB: Al Jazzar
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE:	Omar Jazzar Consulting Engineers
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Volatile Organic Compound (VOC) - 9.6 g/L		
VOC CONTENT	ANSI/BIFMA M7.1 Standard Test Method for Determining VOC Emissions - X7.1-2011 FES Test method	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2023-05-11	CERTIFIER OR LAB: Al Jazzar
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE:	Consulting Engineers
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: VOC - 9.6 g/l. Tested in accordance with ASTM D2369 and ASTM D 3960		
LCA	Environmental Product Declaration (EPD) by the Green Standard	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2023-05-30	CERTIFIER OR LAB: Environmental
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE: 2028-05-30	Footprint Institute
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Environmental Product Declaration has been developed by GCAS Quality Certifications and verified by a third-party verifier at Environmental Footprint Institute, Spain.		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

The original sealed bag of Vetoproof UM766 has a shelf life of 6 months, provided it is stored in original sealed containers clear of ground in a dry and shaded place below 35°C. Some people are sensitive to resins, hardeners, and solvents. Wear suitable protective clothing, gloves, and eye protection. If working in confined areas, appropriate respiratory protective equipment must be used. The use of barrier creams provides additional skin protection. In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent. In case of contact with the eyes, rinse immediately with plenty of clean water and seek medical advice. If swallowed, seek medical attention immediately - Do not induce vomiting.

Vetoproof UM766 is flammable, do not use it near open flames.

MANUFACTURER INFORMATION

MANUFACTURER: Saudi Vetonit Co.Ltd
ADDRESS: P.O. Box 52235
 Riyadh - 11563, Saudi Arabia
WEBSITE: www.saveto.com

CONTACT NAME: Mr. Majid R Al Momani
TITLE: Research & Development Manager
PHONE: +966 11 265 3334
EMAIL: mmomani@saveto.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.