

HPD UNIQUE IDENTIFIER: 448861184

CLASSIFICATION: 09 96 00 High-Performance Coatings

PRODUCT DESCRIPTION: Vetorel XT421 is a single-component, low viscosity pale straw-colored liquid composed of synthetic mineral oils and special varied additives that perform superior to standard oil-based mold release agents. Vetorel XT421 provides the plywood surface with a water-repellent film preventing concrete from adhering to the formwork resulting in a smooth, stainless concrete surface.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	<i>For all contents above the threshold, the manufacturer has:</i>
☒ Nested Materials Method	☐ 100 ppm	☐ Completed	Characterized ☒ Yes ☐ No
☐ Basic Method	☒ 1,000 ppm	☒ Not Completed	<i>Provided weight and role.</i>
Threshold Disclosed Per	☐ Per GHS SDS	Explanation(s) provided for Residuals/Impurities?	Screened ☒ Yes ☐ No
☐ Material	☐ Other	☒ Yes ☐ No	<i>Provided screening results using HPDC-approved methods.</i>
☒ Product			Identified ☒ Yes ☐ No
			<i>Provided name and CAS RN or other identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | **MATERIAL OR SUBSTANCE** | *RESIDUAL OR IMPURITY*

GREENSCREEN SCORE | HAZARD TYPE

VETOREL XT421 [**FUELS, DIESEL** **LT-P1** | MUL | CAN]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.3 and discloses hazards associated with all substances present at or above 1000 parts per million (ppm) in the finished product, along with the role and percent weight. Therefore, this HPD is consistent with the LEED v4.1 MR Credit Building Product Disclosure and Optimization: Material Ingredient Reporting (Option 1).

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): 17.4Regulatory (g/l): 450

Does the product contain exempt VOCs: No

Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario

VOC content: ANSI/BIFMA M7.1 Standard Test Method for Determining VOC Emissions - X7.1-2011 FES Test method

LCA: Environmental Product Declaration (EPD) by the Green Standard

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4.1 Option 1.

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2023-03-18
☐ Yes	VERIFIER:	PUBLISHED DATE: 2023-05-30
☒ No	VERIFICATION #:	EXPIRY DATE: 2026-03-18

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

VETOREL XT421		%: 100.0000	
PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: No	MATERIAL TYPE: Other: Primers & Ancillary	
RESIDUALS AND IMPURITIES NOTES: No residuals or impurities are considered.			
OTHER MATERIAL NOTES: All substances in this material are below the reportable threshold.			

FUELS, DIESEL

ID: 68334-30-5

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-03-22 12:26:32		
%: 70.0000 - 90.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Structure component
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
MUL	German FEA - Substances Hazardous to Waters		Class 2 - Hazard to Waters	
CAN	EU - GHS (H-Statements) Annex 6 Table 3-1		H351 - Suspected of causing cancer [Carcinogenicity - Category 2]	
CAN	EU - Annex VI CMRs		Carcinogen Category 2 - Suspected human Carcinogen	
CAN	GHS - Australia		H351 - Suspected of causing cancer [Carcinogenicity - Category 2]	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	

SUBSTANCE NOTES:

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS		CDPH Standard Method V1.2 (Section 01350/CHPS) - Classroom & Office scenario
CERTIFYING PARTY: Third Party	ISSUE DATE: 2020-08-30	CERTIFIER OR LAB: Al Jazzar
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE:	Omar Jazzar Consulting Engineers
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Volatile Organic Compound (VOC) - 17.4 gm/litter		
VOC CONTENT		ANSI/BIFMA M7.1 Standard Test Method for Determining VOC Emissions - X7.1-2011 FES Test method
CERTIFYING PARTY: Third Party	ISSUE DATE: 2020-08-30	CERTIFIER OR LAB: Al Jazzar
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE:	Consulting Engineers
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: VOC -17.4 g/l. Tested in accordance with ASTM D2369 and ASTM D 3960		
LCA		Environmental Product Declaration (EPD) by the Green Standard
CERTIFYING PARTY: Third Party	ISSUE DATE: 2023-05-30	CERTIFIER OR LAB: Environmental
APPLICABLE FACILITIES: Saudi Arabia	EXPIRY DATE: 2028-05-30	Footprint Institute
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Environmental Product Declaration has been developed by GCAS Quality Certifications and verified by a third-party verifier at Environmental Footprint Institute, Spain.		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

The original sealed container of Vetorel XT421 and has a shelf life of 12 months, provided it is stored clear of ground in a dry, shaded place below 35°C. Vetorel XT421 contains hydrocarbon oils and should be treated as potentially harmful as there is a possible risk of irreversible effects in contact with the skin. Vetorel XT421 should not be swallowed or allowed to come into contact with skin and eyes. Avoid inhalation of vapors and ensure adequate ventilation. Wear suitable gloves and eye/face protection. Should accidental skin contact occur, remove immediately with soap and water - do not use solvent. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; if swallowed, seek medical attention immediately - do not induce vomiting.

MANUFACTURER INFORMATION

MANUFACTURER: Saudi Vetoni Co.Ltd
ADDRESS: P.O. Box 52235
 Riyadh - 11563, Saudi Arabia
WEBSITE: www.saveto.com

CONTACT NAME: Mr. Majid R Al Momani
TITLE: Research & Development Manager
PHONE: +966 11 265 3334
EMAIL: mmomani@saveto.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.