

HPD UNIQUE IDENTIFIER: 36905823232

CLASSIFICATION: 03 01 30 Maintenance of Cast-in-Place Concrete

PRODUCT DESCRIPTION: Patchwell is a single component, polymer-modified, horizontal repair mortar. Patchwell contains a combination of special cements, corrosion inhibitors, dry powdered polymer latex, dispersing and plasticizing agents. It is a powder material, ready to use with the addition of only water. Patchwell is ideally suited for skim coating an existing slab, for spall repairs, and other types of general concrete restoration.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	<i>For all contents above the threshold, the manufacturer has:</i>
☒ Nested Materials Method	☒ 100 ppm	Completed in 4 of 4 Materials	Characterized ☒ Yes ☐ No
☐ Basic Method	☐ 1,000 ppm	Explanation(s) provided for Residuals/Impurities?	<i>Provided weight and role.</i>
Threshold Disclosed Per	☐ Per GHS SDS	☒ Yes ☐ No	Screened ☒ Yes ☐ No
☐ Material	☐ Other		<i>Provided screening results using HPDC-approved methods.</i>
☒ Product			Identified ☒ Yes ☐ No
			<i>Provided name and CAS RN or other identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SAND [QUARTZ BM-1 | CAN | MAM | GEN] CEMENT [PORTLAND CEMENT LT-P1 | CAN | END | MAM LIME BM-2 | SKI | MAM | EYE SILICON DIOXIDE BM-1 | CAN | MAM ALUMINUM OXIDE BM-2 | MAM FERRIC OXIDE BM-1 | CAN | MAM | EYE | SKI SULFUR TRIOXIDE BM-2 | MAM MAGNESIUM OXIDE BM-3dg | CAN] SLAG CEMENT [LIME BM-2 | SKI | MAM | EYE MAGNESIUM OXIDE BM-3dg | CAN QUARTZ BM-1 | CAN | MAM | GEN] FILLER [EMERY LT-UNK]

Number of Greenscreen BM-4/BM3 contents ... 2

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... BM-1, LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This HPD was produced using primary information from the manufacturer, including CAS numbers and SDS when needed. Every effort has been made to report the substances in this product by the manufacturer to the listed threshold. This is a voluntary, self-reported effort. Any errors or omissions shall be considered a human error and therefore reported to the manufacturer. The manufacturer shall not be liable for omissions.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: Inherently non-emitting source per LEED

VOC content: MAS Certified Green - VOC Content

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Option 1.

Pre-checked for LEED v4.1 Option 1.

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2023-05-21
☐ Yes	VERIFIER:	PUBLISHED DATE: 2023-06-01
☒ No	VERIFICATION #:	EXPIRY DATE: 2026-05-21

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

SAND

%: 60.0000 - 70.0000

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Geologically Derived Material

RESIDUALS AND IMPURITIES NOTES:

Impurities listed above the threshold by Quartz or Pharos databases are noted in this HPD. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES:

Impurities listed above the threshold by Quartz or Pharos databases are noted in this HPD.

QUARTZ

ID: 14808-60-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2023-05-21 23:51:08

%: 99.0000 - 100.0000

GreenScreen: BM-1

RC: UNK

NANO: No

SUBSTANCE ROLE: Filler

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CAN	IARC	Group 1 - Agent is Carcinogenic to humans
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]
CAN	GHS - New Zealand	Carcinogenicity category 1
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Per Pharos: "Only a few elements can replace silicon in the quartz lattice (substitutional positions) or are small enough to occupy free spaces in the lattice (interstitial positions). In natural quartz crystals, the most common ones to replace Si are Al, Fe, Ge, and Ti, whereas Li, Na, Ca, Mg and Fe often occupy interstitial positions in the "c-channels"." [Mindat]

CEMENT	%: 25.0000 - 35.0000	
PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Geologically Derived Material

RESIDUALS AND IMPURITIES NOTES: Impurities listed above the threshold by Quartz or Pharos databases are noted in this HPD. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES: According to the Pharos database Portland cement has 14 different known or potential residuals and impurities. Only substances with a known presence above the 0.1 thresholds will be in this HPD and should be noted that they are for reference only. The presence of any of these residuals is unknown in the actual material. No testing has been conducted on the actual material.

PORTLAND CEMENT

ID: 65997-15-1

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-22 0:06:32		
%: 75.0000	GreenScreen: LT-P1	RC: UNK	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
CAN	MAK		Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification	
END	TEDX - Potential Endocrine Disruptors		Potential Endocrine Disruptor	
MAM	GHS - Japan		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	

SUBSTANCE NOTES: By the TSCA Definition 2008: Portland cement is a mixture of chemical substances produced by burning or sintering at high temperatures (greater than 1200.degree.C (2192.degree.F)) raw materials which are predominantly calcium carbonate, aluminum oxide, silica, and iron oxide. The chemical substances which are manufactured are confined in a crystalline mass. This category includes all of the chemical substances specified below when they are intentionally manufactured in the production of Portland cement. The primary members of the category are Ca2SiO4 and Ca3SiO5. Other compounds listed below may also be included in combination with these primary substances.: CaAl2O4; CaAl4O7; CaAl12O1; Ca3Al2O6; Ca12Al14O33; CaO; Ca2Fe2O5; Ca2Al2SiO7; Ca4Al6SO16; Ca12Al14Cl2O32; Ca12Al14F2O32; Ca4Al2Fe2O10; Ca6A14Fe2O15 (National Library of Medicine Record)

LIME

ID: 1305-78-8

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-25 2:27:49		
%: Impurity/Residual	GreenScreen: BM-2	RC: UNK	NANO: No	SUBSTANCE ROLE: Impurity/Residual

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
SKI	GHS - Australia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Japan	H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]
SKI	GHS - New Zealand	Skin corrosion category 1C
EYE	GHS - New Zealand	Serious eye damage category 1
EYE	GHS - Japan	H318 - Causes serious eye damage [Serious eye damage / eye irritation - Category 1]
SKI	GHS - Japan	H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]
EYE	GHS - Australia	H318 - Causes serious eye damage [Serious eye damage/eye irritation - Category 1]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes of Problematic Chemicals Antimicrobials
SUBSTANCE NOTES: Calcium Oxide = 64% mass fraction of Portland Cement (NIST MSDS)- Per Pharos database.		

SILICON DIOXIDE

ID: 7631-86-9

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-25 2:27:06		
%: Impurity/Residual	GreenScreen: BM-1	RC: UNK	NANO: No	SUBSTANCE ROLE: Impurity/Residual
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]		
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes of Problematic Chemicals Antimicrobials		

SUBSTANCE NOTES: Silicon dioxide = 20% mass fraction of Portland Cement (NIST MSDS)- Per Pharos database.

ALUMINUM OXIDE

ID: 1344-28-1

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-25 2:26:24		
%: Impurity/Residual	GreenScreen: BM-2	RC: UNK	NANO: No	SUBSTANCE ROLE: Impurity/Residual
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022		
		Biological and Environmentally Released Materials		
RESTRICTED LIST	Cradle to Cradle Products Innovation Institute (C2CPII)	C2C Certified v4 Product Standard Restricted Substances List (RSL) - Effective July 1, 2022		
		Children's Products		

SUBSTANCE NOTES: Aluminum Oxide = 4% mass fraction of Portland Cement (NIST MSDS)- Per Pharos database.

FERRIC OXIDE

ID: 1309-37-1

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-25 2:23:01		
%: Impurity/Residual	GreenScreen: BM-1	RC: UNK	NANO: No	SUBSTANCE ROLE: Impurity/Residual
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
EYE	GHS - Japan	H318 - Causes serious eye damage [Serious eye damage / eye irritation - Category 1]		
SKI	GHS - Japan	H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: Ferric Oxide = 4% mass fraction of Portland Cement (NIST MSDS)- Per Pharos database.

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-25 2:22:20		
%: Impurity/Residual	GreenScreen: BM-2	RC: UNK	NANO: No	SUBSTANCE ROLE: Impurity/Residual
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
MAM	US EPA - EPCRA Extremely Hazardous Substances		Extremely Hazardous Substances	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	
SUBSTANCE NOTES: Sulfur trioxide = 3% mass fraction of Portland Cement (NIST MSDS)- Per Pharos database.				

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-25 2:21:35		
%: Impurity/Residual	GreenScreen: BM-3dg	RC: UNK	NANO: Unknown	SUBSTANCE ROLE: Impurity/Residual
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
CAN SLAG CEMENT	MAK %: 3.0000 - 6.0000		Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels	
PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes		MATERIAL TYPE: Geologically Derived Material	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	

RESIDUALS AND IMPURITIES NOTES: Impurities listed above the threshold by Quartz or Pharos databases are noted in this HPD. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

SUBSTANCE NOTES: Magnesium Oxide = 1 % mass fraction of Portland Cement (NIST MSDS)- Per Pharos database.

OTHER MATERIAL NOTES:

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-22 0:19:00		
%: 50.0000 - 60.0000	GreenScreen: BM-2	RC: UNK	NANO: No	SUBSTANCE ROLE: Filler

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
SKI	GHS - Australia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Japan	H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]
SKI	GHS - New Zealand	Skin corrosion category 1C
EYE	GHS - New Zealand	Serious eye damage category 1
EYE	GHS - Japan	H318 - Causes serious eye damage [Serious eye damage / eye irritation - Category 1]
SKI	GHS - Japan	H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]
EYE	GHS - Australia	H318 - Causes serious eye damage [Serious eye damage/eye irritation - Category 1]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	Green Science Policy Institute (GSPI)	GSPI - Six Classes of Problematic Chemicals Antimicrobials
SUBSTANCE NOTES: Calcium Oxide (CAS No. 1305-78-8) = 50-60% mass fraction of blast furnace slag (NIST MSDS)- Per Pharos database.		

MAGNESIUM OXIDE

ID: 1309-48-4

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-22 0:24:31		
%: 18.0000 - 35.0000	GreenScreen: BM-3dg	RC: UNK	NANO: No	SUBSTANCE ROLE: Filler
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
CAN	MAK		Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: Magnesium Oxide = 18-30% mass fraction of blast furnace slag (NIST MSDS)- Per Pharos database.				

QUARTZ

ID: 14808-60-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-05-22 0:29:14		
%: 1.0000 - 10.0000	GreenScreen: BM-1	RC: UNK	NANO: No	SUBSTANCE ROLE: Filler

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CAN	IARC	Group 1 - Agent is Carcinogenic to humans
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]
CAN	GHS - New Zealand	Carcinogenicity category 1
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Slag may contain trace amounts of, quartz, manganese oxide, titanium oxide, chromium compounds, sulfur compounds, and other trace compounds.

FILLER	%: 0.7500 - 1.2500	
PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Geologically Derived Material
RESIDUALS AND IMPURITIES NOTES: Impurities listed above the threshold by Quartz or Pharos databases are noted in this HPD. Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.		

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2023-05-30 13:19:10

%: 100.0000

GreenScreen: LT-UNK

RC: UNK

NANO: No

SUBSTANCE ROLE: Abrasive

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Emery ore that is rich in aluminum oxide. Mineralogically, Emery is an intimate mix of corundum and magnetite. Corundum is a natural form of aluminum oxide. Emery ore that contains not less than 58% aluminum oxide.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Inherently non-emitting source per LEED	
CERTIFYING PARTY: Self-declared	ISSUE DATE: 2023-06-01	CERTIFIER OR LAB: None
APPLICABLE FACILITIES: This is not a facility based declaration.	EXPIRY DATE:	
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES:		

VOC CONTENT	MAS Certified Green - VOC Content	
CERTIFYING PARTY: Self-declared	ISSUE DATE: 2023-06-01	CERTIFIER OR LAB: Kaufman
APPLICABLE FACILITIES: This is not facility based.	EXPIRY DATE:	Products
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: This is not MAS Green certified. VOC content is self declared using the US EPA and SCAQD self calculation method.		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

No accessories are included with this product.

- APPLICATIONS:
- Spall Repair
 - Skim Coating
 - Residential Concrete Repairs
 - Horizontal Concrete Repairs
 - Industrial Maintenance
 - Commercial Construction

PRECAUTIONS:

Avoid air entrapment caused by excessive mixing. Do not add excessive amounts of water, as this will weaken the mortar. Over troweling results in discoloration and a weak cracked surface. Do not apply when substrate or ambient temperatures are below 40°F. Read the complete Product Data Sheet, Safety Data Sheet, and Concrete Substrate Preparation Guidelines before using.

PACKAGING:

50-lb. Bags (.45 ft3)

MANUFACTURER INFORMATION

MANUFACTURER: Kaufman Products, Inc.
ADDRESS: 3811 Curtis Avenue
 Baltimore Maryland 21226, United States
WEBSITE: <https://www.kaufmanproducts.net>

CONTACT NAME: Alex Kaufman
TITLE: President
PHONE: 410-354-8600
EMAIL: akaufman@kaufmanproducts.net

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.