

HPD UNIQUE IDENTIFIER: 2121908150272

CLASSIFICATION: 07 16 13 Polymer Modified Cement Waterproofing

PRODUCT DESCRIPTION: Sikalastic®-152 is a two component fibre-reinforced mortar, with very low elastic modulus, based on cement modified with special alkali-resistant polymers, containing fine particle size selected aggregates and adequate additives for waterproofing and protection of concrete subgrades subject to flexural strain. Sikalastic®-152 is particularly advisable for application in humid environments or low temperature conditions.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	<i>For all contents above the threshold, the manufacturer has:</i>
☒ Nested Materials Method	☐ 100 ppm	Completed in 2 of 2 Materials	Characterized ☒ Yes ☐ No
☐ Basic Method	☒ 1,000 ppm	Explanation(s) provided for Residuals/Impurities?	<i>Provided weight and role.</i>
Threshold Disclosed Per	☐ Per GHS SDS	☒ Yes ☐ No	Screened ☒ Yes ☐ No
☐ Material	☐ Other		<i>Provided screening results using HPDC-approved methods.</i>
☒ Product			Identified ☐ Yes ☒ No
			<i>Provided name and CAS RN or other identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | **MATERIAL OR SUBSTANCE** | *RESIDUAL OR IMPURITY*

GREENSCREEN SCORE | HAZARD TYPE

SIKALASTIC®-152 COMP A [**UNDISCLOSED** **LT-UNK** **UNDISCLOSED** **BM-4** **UNDISCLOSED** **LT-UNK**] **SIKALASTIC®-152 COMP B** [**UNDISCLOSED** **BM-1 *** CAN | MAM | GEN **UNDISCLOSED** **LT-UNK** **UNDISCLOSED** **LT-P1**] CAN | END | MAM]

Number of Greenscreen BM-4/BM3 contents ... 1

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Materials listed as Undisclosed is done to preserve integrity of formula and maintain competitive advantage

*Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. For this reason, this score is intentionally omitted from the "Contents highest concern" line above. See HPDC's Special Conditions policy for more information.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): <1 Regulatory (g/l): 100

Does the product contain exempt VOCs: No

Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

CERTIFICATIONS AND COMPLIANCE *See Section 3 for additional listings.*

VOC emissions: Emicode EC1 PLUS- very low emission

VOC content: SCAQMD Rule 1113 Architectural Coatings - Concrete curing compounds, Industrial Maintenance (IM) Coatings, Zinc-Rich IM Primers, Primers, Sealers, and Undercoaters, including Quick-Dry Primers, Sealers, and Undercoaters and Specialty Primers, Rust Prevent

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Option 1.

Pre-checked for LEED v4.1 Option 1.

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2024-09-24
☐ Yes	VERIFIER:	PUBLISHED DATE: 2024-09-24
☒ No	VERIFICATION #:	EXPIRY DATE: 2027-09-24

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

SIKALASTIC®-152 COMP A

%: 70.0000 - 80.0000

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities are determined based on information provided in supplier documentation. All residuals and impurities within the threshold are included.

OTHER MATERIAL NOTES:

UNDISCLOSED

ID: Undisclosed

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2024-09-24 7:59:27

%: 40.0000 - 45.0000

GreenScreen: LT-UNK

RC: None

NANO: No

SUBSTANCE ROLE: Binder

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards

UNDISCLOSED

ID: Undisclosed

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2024-09-24 7:59:27

%: 30.0000 - 35.0000

GreenScreen: BM-4

RC: None

NANO: No

SUBSTANCE ROLE: Solvent

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions

Exempted from REACH Annex IV listing due to intrinsic safety

SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards

UNDISCLOSED

ID: Undisclosed

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2024-09-24 7:59:27

%: 20.0000 - 30.0000

GreenScreen: LT-UNK

RC: None

NANO: No

SUBSTANCE ROLE: Binder

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards.

SIKALASTIC®-152 COMP B

%: 20.0000 - 30.0000

PRODUCT THRESHOLD: 1000 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Other: portland cement, aggregates and additives
--------------------------------	---	---

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities are determined based on information provided in supplier documentation. All residuals and impurities within the threshold are included.

OTHER MATERIAL NOTES:

UNDISCLOSED

ID: Undisclosed

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2024-09-24 7:59:27

%: 65.0000 - 70.0000

GreenScreen: BM-1

RC: None

NANO: No

SUBSTANCE ROLE: Filler

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen**
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route**
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)**
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man**
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources**
CAN	IARC	Group 1 - Agent is Carcinogenic to humans**
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen**
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]**
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]**
CAN	GHS - New Zealand	Carcinogenicity category 1**
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]**
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]**
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1**

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards

**Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.

This substance is part of a powder or aerosol; however, its potential for respiration is limited, as demonstrated by this [report or certification](#)

UNDISCLOSED		ID: Undisclosed	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2024-09-24 7:59:28	
%: 20.0000 - 30.0000	GreenScreen: LT-UNK	RC: PreC	NANO: No
		SUBSTANCE ROLE: Binder	

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists
SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards.		

UNDISCLOSED

ID: Undisclosed

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2024-09-24 7:59:27		
?: 3.0000 - 7.0000	GreenScreen: LT-P1	RC: PostC	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor		
MAM	GHS - Japan	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Emicode EC1 PLUS- very low emission	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2022-12-15 00:00:00	CERTIFIER OR LAB: Eurofins
APPLICABLE FACILITIES: Sika Hellas at Kryoneri, Athens, Greece	EXPIRY DATE:	
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES:		
VOC CONTENT	SCAQMD Rule 1113 Architectural Coatings - Concrete curing compounds, Industrial Maintenance (IM) Coatings, Zinc-Rich IM Primers, Primers, Sealers, and Undercoaters, including Quick-Dry Primers, Sealers, and Undercoaters and Specialty Primers, Rust Prevent	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2022-12-22 00:00:00	CERTIFIER OR LAB: Eurofins
APPLICABLE FACILITIES: Sika Hellas at Kryoneri, Athens, Greece	EXPIRY DATE:	
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Product Type declared by SCAQMD 1113 is Waterproofing Sealers		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

USES

- Waterproofing and protection of hydraulic structures such as: basins, tanks, swimming pools, concrete piping, bridges and canals
- Waterproofing and protection of outer walls to be buried into the ground
- Inside waterproofing of light counter pressure water, of walls and floors in basements
- Waterproofing of terraces and balconies with concrete or old tiles subgrades
- Waterproofing of weather exposed surfaces
- Protective, flexible, anti-carbonation coating of concrete surfaces also damaged from plastic and hydraulic shrinkage
- Flexible coating of concrete structures, also subjected to flexural strain
- Concrete surface protection, in accordance with the following EN 1504-9. Principles: 1: protection against ingress (coating); 2: moisture control (coating); 8: increase of resistivity (coating)

CHARACTERISTICS/ ADVANTAGES

- Flexible waterproofing and concrete protection with one product
- Reliable application also in very humid environment
- Applicable also on lightly humid subgrades
- Non sagging: easy application also on vertical walls
- Fast curing (also at low temperature)
- Crack bridging properties
- Excellent adhesion onto almost all subgrades, such as for instance concrete, cement mortars, stone, ceramics, bricks and wood
- High resistance against de-icing salts and carbon dioxide

APPROVALS/ STANDARDS

- Fiber reinforced, two component, cement based mortar for waterproofing and concrete protection according to EN 1504-2, Principles 1,2 and 8 (Methods

1.3, 2.2, 8.2 of EN 1504-9)

- 2-component, cementitious mortar for waterproofing beneath bonded tiles (bonded with a C2 adhesive according to EN 12004) with improved crack bridging ability at low temperature (-200

C) and resistant to contact with chlorinated water, complying to the performance of CMO2P class of EN 14891:2012.

- DoP 020701010020000043 1026, certificated by the Factory Production Control Body 0546 and from the notified lab 01599 and provided with the CE Mark.

MANUFACTURER INFORMATION

MANUFACTURER: **SIKA Hellas**
 ADDRESS: **Protomagias 15**
Athens, Attica 14568
 COUNTRY: **Greece**

WEBSITE: **http://grc.sika.com/**
 CONTACT NAME: **Aggeliki Zacharopoulou**
 TITLE: **EHS-QA-Manager**
 PHONE: **2111080246**
 EMAIL: **zacharopoulou.aggeliki@gr.sika.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold	Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold	Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold	Substances listed individually per threshold indicated per product

Nano	Composed of nano scale particles or nanotechnology
Third Party Verified	Verification by independent certifier approved by HPDC
Preparer	Third party preparer, if not self-prepared by manufacturer
Applicable facilities	Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and

