

HPD UNIQUE IDENTIFIER: 1453384704

CLASSIFICATION: 03 35 00 Concrete Finishing

PRODUCT DESCRIPTION: Sikafloor®-3 QuartzTop GR is a one part, preblended, coloured mineral dry shake hardener for concrete comprising of cement, specially selected quartz mineral aggregates and admixtures.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	<i>For all contents above the threshold, the manufacturer has:</i>
☐ Nested Materials Method	☐ 100 ppm	☒ Completed	Characterized ☒ Yes ☐ No
☒ Basic Method	☒ 1,000 ppm	☐ Partially Completed	<i>Provided weight and role.</i>
Threshold Disclosed Per	☐ Per GHS SDS	☐ Not Completed	Screened ☒ Yes ☐ No
☐ Material	☐ Other	Explanation(s) provided :	<i>Provided screening results using HPDC-approved methods.</i>
☒ Product		☒ Yes ☐ No	Identified ☐ Yes ☒ No
			<i>Provided name and CAS RN or other identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE
SIKAFLOOR®-3 QUARTZTOP GR | UNDISCLOSED BM-1 * | CAN |
MAM | GEN UNDISCLOSED LT-P1 | CAN | END | MAM]

Number of Greenscreen BM-4/BM3 contents ... 0
Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1
Nanomaterial ... No
INVENTORY AND SCREENING NOTES:

Materials listed as Undisclosed is done to preserve integrity of formula and maintain competitive advantage

*Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. For this reason, this score is intentionally omitted from the "Contents highest concern" line above. See HPDC's Special Conditions policy for more information.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): <1 Regulatory (g/l): 50
Does the product contain exempt VOCs: No
Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.
VOC emissions: Emicode EC1 PLUS- very low emission
VOC content: SCAQMD Rule 1113 Architectural Coatings - Concrete curing compounds, Industrial Maintenance (IM) Coatings, Zinc-Rich IM Primers, Primers, Sealers, and Undercoaters, including Quick-Dry Primers, Sealers, and Undercoaters and Specialty Primers, Rust Prevent

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Option 1.
Pre-checked for LEED v4.1 Option 1.

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2024-09-25
☐ Yes	VERIFIER:	PUBLISHED DATE: 2024-09-25
☒ No	VERIFICATION #:	EXPIRY DATE: 2027-09-25

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

SIKAFLOOR®-3 QUARTZTOP GR

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities are determined based on information provided in supplier documentation. All residuals and impurities within the threshold are included

OTHER PRODUCT NOTES:

UNDISCLOSED

ID: Undisclosed

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-09-25 3:50:56	
%: 60.0000 - 80.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Filler
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
CAN	US CDC - Occupational Carcinogens		Occupational Carcinogen**	
CAN	CA EPA - Prop 65		Carcinogen - specific to chemical form or exposure route**	
CAN	US NIH - Report on Carcinogens		Known to be Human Carcinogen (respirable size - occupational setting)**	
CAN	MAK		Carcinogen Group 1 - Substances that cause cancer in man**	
CAN	IARC		Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources**	
CAN	IARC		Group 1 - Agent is Carcinogenic to humans**	
CAN	US NIH - Report on Carcinogens		Known to be a human Carcinogen**	
CAN	GHS - Japan		H350 - May cause cancer [Carcinogenicity - Category 1A]**	
CAN	GHS - Australia		H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]**	
CAN	GHS - New Zealand		Carcinogenicity category 1**	
MAM	GHS - Japan		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**	
GEN	GHS - Japan		H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]**	
MAM	GHS - Australia		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]**	
MAM	GHS - New Zealand		Specific target organ toxicity - repeated exposure category 1**	

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists
SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards. **Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information. This substance is part of a powder or aerosol; however, its potential for respiration is limited, as demonstrated by this report or certification		

UNDISCLOSED

ID: **Undisclosed**

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2024-09-25 3:50:56**

%: **25.0000 - 35.0000**

GreenScreen: **LT-P1**

RC: **PreC**

NANO: **No**

SUBSTANCE ROLE: **Binder**

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor
MAM	GHS - Japan	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Emicode EC1 PLUS- very low emission	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2022-12-21 00:00:00	CERTIFIER OR LAB: Eurofins
APPLICABLE FACILITIES: Sika Hellas at Kryoneri, Athens, Greece	EXPIRY DATE:	
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES:		

VOC CONTENT	SCAQMD Rule 1113 Architectural Coatings - Concrete curing compounds, Industrial Maintenance (IM) Coatings, Zinc-Rich IM Primers, Primers, Sealers, and Undercoaters, including Quick-Dry Primers, Sealers, and Undercoaters and Specialty Primers, Rust Prevent	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2022-12-22 00:00:00	CERTIFIER OR LAB: Eurofins
APPLICABLE FACILITIES: Sika Hellas at Kryoneri, Athens, Greece	EXPIRY DATE:	
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Product type declared by SCAQMD 1113 is Concrete Surface Retarder		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

USES

Sikafloor®-3 QuartzTop GR may only be used by experienced professionals.

- Sikafloor®-3 QuartzTop GR provides a hard wearing, mineral dry shake topping for monolithic floors. When sprinkled and trowelled onto fresh wet concrete floors, it forms a wear resistant smooth surface.
- Typical uses are in warehouses, factories, shopping malls, where wear durable and wear resistant floor is the key requirement.

CHARACTERISTICS / ADVANTAGES

- Medium wear resistance rating
- Impact resistance
- Dust proof
- Cost effective surface hardener
- Fast application
- Increased resistance to oils and grease
- Quality assured factory blending
- Easy cleaning
- Wide range of colours

APPROVALS / CERTIFICATES

CE Marking and Declaration of Performance to
EN 13813 - Screed material and floor screeds. Class
CT-C70-F7-AR1

MANUFACTURER INFORMATION

MANUFACTURER: **SIKA Hellas**
ADDRESS: **Protomagias 15**
Athens, Attica 14568
COUNTRY: **Greece**

WEBSITE: **<http://grc.sika.com/>**
CONTACT NAME: **Aggeliki Zacharopoulou**
TITLE: **EHS-QA-Manager**
PHONE: **2111080246**
EMAIL: **zacharopoulou.aggeliki@gr.sika.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY**Hazard Types**

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and

