

HPD UNIQUE IDENTIFIER: 1561353216

CLASSIFICATION: 07 25 00 Weather Barriers

PRODUCT DESCRIPTION: TRM Sill is an adhesive sealant barrier designed to prevent termites from accessing wood framing members from a concrete crack or joint in the floor. It adheres to the concrete subfloor and blocks termite access to the sill.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	<i>For all contents above the threshold, the manufacturer has:</i>
☐ Nested Materials Method	☐ 100 ppm	☒ Completed	Characterized ☒ Yes ☐ No
☒ Basic Method	☒ 1,000 ppm	☐ Partially Completed	<i>Provided weight and role.</i>
Threshold Disclosed Per	☐ Per GHS SDS	☐ Not Completed	Screened ☒ Yes ☐ No
☐ Material	☐ Other	Explanation(s) provided :	<i>Provided screening results using HPDC-approved methods.</i>
☒ Product		☒ Yes ☐ No	Identified ☒ Yes ☐ No
			<i>Provided name and CAS RN or other identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | **MATERIAL OR SUBSTANCE** | *RESIDUAL OR IMPURITY*

GREENSCREEN SCORE | HAZARD TYPE

TRM SILL [**ASPHALT** **LT-1**] CAN | MAM | GEN **STYRENE BUTADIENE RUBBER (SBR)** **LT-UNK** **BENZENE, ETHENYL-, POLYMER WITH 2-METHYL-1,3-BUTADIENE** **LT-UNK** **POLYETHYLENE** **LT-UNK** **QUARTZ** **BM-1**] CAN | MAM | GEN]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-1, BM-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

All component hazard listed are based on individual compounds not the entire product. The components listed below are blended together to form a sheet product which is classified as an article under GHS.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE *See Section 3 for additional listings.*

VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Option 1.

Pre-checked for LEED v4.1 Option 1.

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2024-08-21
☐ Yes	VERIFIER:	PUBLISHED DATE: 2024-11-27
☒ No	VERIFICATION #:	EXPIRY DATE: 2027-08-21

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

TRM SILL

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: The raw materials used in this product contain residuals at levels less than 1000 ppm.

OTHER PRODUCT NOTES: None

ASPHALT

ID: 8052-42-4

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-08-21 5:35:21		
%: 66.0000 - 72.0000	GreenScreen: LT-1	RC: None	NANO: No	SUBSTANCE ROLE: Binder	
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
CAN	US CDC - Occupational Carcinogens		Occupational Carcinogen		
CAN	MAK		Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
CAN	IARC		Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources		
MAM	GHS - Japan		H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
CAN	GHS - Japan		H351 - Suspected of causing cancer [Carcinogenicity - Category 2]		
MAM	GHS - Japan		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
GEN	GHS - Japan		H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION		
None found			No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: Note this material is not in the molten stage, which generates hazardous asphalt fumes. This raw material is combined with styrenated polymers and fillers, then laminated to create a sheet layer of adhesive sealant which is applied to the structure at ambient temperatures. The finished product is applied, and functions during it's lifetime, at ambient temperatures.

STYRENE BUTADIENE RUBBER (SBR)

ID: 9003-55-8

HAZARD DATA SOURCE: Pharos Chemical and Materials Library	HAZARD SCREENING DATE: 2024-08-21 5:35:21
---	---

%		5.0000 - 9.0000		GreenScreen:	LT-UNK	RC:	None	NANO:	No	SUBSTANCE ROLE:	Polymer species
HAZARD TYPE		LIST NAME AND SOURCE				WARNINGS					
None found						No warnings found on HPD Priority Hazard Lists					
ADDITIONAL LISTINGS		LIST NAME AND SOURCE				NOTIFICATION					
None found						No listings found on Additional Hazard Lists					
SUBSTANCE NOTES: This raw material is an integral part of the finished product.											

BENZENE, ETHENYL-, POLYMER WITH 2-METHYL-1,3-BUTADIENE

ID: 25038-32-8

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-08-21 5:35:21		
%: 3.0000 - 7.0000		GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Polymer species
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
None found			No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION		
None found			No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This raw material is an integral part of the finished product.					

POLYETHYLENE

ID: 9002-88-4

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-08-21 5:35:22		
%: 2.0000 - 4.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Structure component	
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
None found			No warnings found on HPD Priority Hazard Lists		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION		
None found			No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: This raw material is an integral part of the finished product.					

QUARTZ

ID: 14808-60-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-08-21 5:35:22		
%: 0.2000 - 0.5000		GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Impurity/Residual

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources
CAN	IARC	Group 1 - Agent is Carcinogenic to humans
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]
CAN	GHS - New Zealand	Carcinogenicity category 1
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: This material is found as an impurity in Calcium Carbonate

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	N/A	
CERTIFYING PARTY: Self-declared	ISSUE DATE: 2021-04-14 00:00:00	CERTIFIER OR LAB: None
APPLICABLE FACILITIES: All	EXPIRY DATE:	
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Product is a sheet membrane		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

650 LT LIQUID ADHESIVE

MANUFACTURER (OR GENERIC): **Polyguard Products, Inc.**

HPD URL: <https://hpdrepository.hpd-collaborative.org/Pages/Results.aspx#k=polyguard>

ACCESSORY TYPE: Adhesive

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: All substrates must be prepared prior to application of membrane. Apply to a clean, dry, dust free, and frost-free surface. Apply by roller or brush. Apply Polyguard® 650 LT Liquid Adhesive per manufacturer's instructions. Allow to cure per manufacturer's directions.

343 CONSTRUCTION ADHESIVE

MANUFACTURER (OR GENERIC): **Generic**

HPD URL: No HPD available

ACCESSORY TYPE: Adhesive

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: If weather is cold and/or damp, making initial application marginal, application of 343 Construction Adhesive will assist with initial application. The 343 Construction Adhesive may be used in areas of confined spaces.

650 WB LIQUID ADHESIVE

MANUFACTURER (OR GENERIC): **Polyguard Products**

HPD URL: <https://hpdrepository.hpd-collaborative.org/Pages/Results.aspx#k=polyguard>

ACCESSORY TYPE: Adhesive

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: All substrates must be prepared prior to application of membrane. Apply to a clean, dry, dust free, and frost-free surface. Apply by roller or brush. Apply the Polyguard® 650 WB Liquid Adhesive per manufacture directions. Allow to cure per manufacturer's directions.

TRM SEALANT

MANUFACTURER (OR GENERIC): **Polyguard Products**

HPD URL: <https://hpdrepository.hpd-collaborative.org/Pages/Results.aspx#k=polyguard>

ACCESSORY TYPE: Other

CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: TRM Sealant is used to seal on top of slab before framing occurs (a common termite entry point). It also seals overlaps, gaps, and penetrations where TRM membrane barriers are installed.

Section 5: General Notes

Reviewed the SDS for all raw materials used in the production of this product. Performed calculations to determine the percentage of each component including the residuals and impurities. Only reported residuals or impurities that were above the 1000 ppm threshold.

MANUFACTURER INFORMATION

MANUFACTURER: **Polyguard Products**
 ADDRESS: **3801 S I 45**
Ennis, Texas 75119
 COUNTRY: **US**

WEBSITE: **www.Polyguard.com**
 CONTACT NAME: **Chris Rogalski**
 TITLE: **Quality Mgr.**
 PHONE: **214-515-5000**
 EMAIL: **Polyguard@polyguard.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold	Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold	Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold	Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and

