

HPD UNIQUE IDENTIFIER: 343840893376512
HPD UNIQUE PRODUCT ID: Not provided.
CLASSIFICATION: 03 63 00 Epoxy Grouting
PRODUCT TYPE: Cement, Mortar
PRODUCT DESCRIPTION: NanoGrout SG is a high-performance, two-component, epoxy-based structural adhesive and anchor grout designed for anchoring, bonding, and precision structural fixing applications. The system is supplied in paste and pourable grades and, when mixed, produces a dense, cohesive grout with excellent adhesion, gap-filling capability, and strong bonding to concrete and steel substrates. Formulated with calcium carbonate fillers, epoxy resin, polyamide and amine-based hardeners, and performance additives, NanoGrout SG provides controlled rheology, low water absorption, and high chemical resistance without reliance on water. It develops high early and long-term strength, exhibits non-sag behaviour on vertical and overhead surfaces, and maintains durability under static and dynamic loading conditions. Typical applications include anchor bolts, starter bars, base plate bolt pockets, bridge bearings, segmental precast bonding, and structural strengthening works in civil, infrastructure, and industrial projects.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format → Nested Materials Method	Residuals/Impurities Evaluation Completed in 2 of 2 Materials	For all contents above the threshold, the manufacturer has:
Threshold Disclosed Per → Product	Explanation(s) provided for Residuals/Impurities? Yes	Characterized Provided weight and role. Yes
Threshold Level → 100 ppm		Screened Provided screening results using HPDC-approved methods. Yes
		Identified Provided name and CAS RN or other identifier. Yes

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY
GREENSCREEN SCORE | HAZARD TYPE
BASE [BISPHENOL A EPICHLOROHYDRIN POLYMER LT-P1] MUL | SKI | EYE | AQU QUARTZ BM-1 *] CAN | MAM | GEN FUMED SILICA, CRYSTALLINE-FREE, NANO, LACKING HYDROPHOBIC SURFACE TREATMENT BM-1] ALKYL (C12, C14) GLYCIDYL ETHER LT-P1] MUL | SKI] HARDENER [2-CYCLOHEXENE-1-OCTANOIC ACID, 5(OR 6)-CARBOXY-4-HEXYL-, COMPD. WITH 2-AMINO-2-METHYL-1-PROPANOL NoGS TALC BM-1] CAN | MAM QUARTZ BM-1 *] CAN | MAM | GEN POLYETHYLENEDIPOLYAMINE, DIMER FATTY ACID CONDENSATE BM-1] MUL | SKI | EYE TRIETHYLENETETRAMINE LT-P1] SKI | MUL | MAM | EYE | AQU | REP CARBON BLACK BM-1 *] CAN | EYE | MAM | PHY RUTILE TITANIUM DIOXIDE LT-1 *] CAN]

Number of Greenscreen BM-4/BM3 contents ... 0
Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1, BM-1
Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 3.0 and discloses hazards associated with all substances present at or above 100 parts per million (ppm) in the finished product, along with the role and percent weight. Therefore, this HPD is consistent with the LEED v4.1 MR Credit Building Product Disclosure and Optimization: Material Ingredient Reporting (Option 1).

*Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. For this reason, this score is intentionally omitted from the "Contents highest concern" line above. See HPDC's Special Conditions policy for more information.

PFAS DETAILS:

This product does not contain intentionally added PFAS, but it is unknown if PFAS is contained in materials or substances from suppliers.

Attestation:



2026-02-10

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

COMPLIANCE *See Section 3 for additional listings.*

VOC emissions: CDPH Standard Method - Not tested

Management: ISO 9001:2015 Quality management systems

Management: ISO 14001:2015 - Environmental management systems

Management: ISO 45001:2018 Occupational health and safety management systems

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4.1 Option 1.

Pre-checked for LEED v5 Human Health 1.

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 3.0, available on the HPDC website at: www.hpd-collaborative.org/hpd-3-0-standard

BASE		%: 60.0000 - 75.0000	
PRODUCT THRESHOLD: 100 ppm		RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Polymeric Material
RESIDUALS AND IMPURITIES NOTES: CONMIX LTD. worked with the HPDC Approved Preparer to confirm that all residuals and impurities were considered under the preparation of this HPD. This was accomplished by obtaining full formulation disclosure, including residuals and impurities, down to the 100 ppm threshold.			
OTHER MATERIAL NOTES: All substances in this material are below the reportable threshold.			

BISPHENOL A EPICHLOROHYDRIN POLYMER			ID: 25068-38-6	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-03-17 10:19:32	
%: 30.0000 - 80.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Binder

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
EYE	EU - GHS (H-Statements) Annex 6 Table 3-1	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
AQU	EU - GHS (H-Statements) Annex 6 Table 3-1	H411 - Toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 2]
EYE	GHS - New Zealand	Eye irritation category 2
SKI	GHS - Australia	H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]
EYE	GHS - Australia	H319 - Causes serious eye irritation [Serious eye damage/eye irritation - Category 2A]
SKI	GHS - Japan	H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]
SKI	GHS - New Zealand	Skin sensitisation category 1
AQU	GHS - New Zealand	Hazardous to the aquatic environment - chronic category 2
AQU	GHS - Japan	H400 - Very toxic to aquatic life [Hazardous to the aquatic environment (acute) - Category 1]
AQU	GHS - Japan	H410 - Very toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 1]
AQU	GHS - Australia	H411 - Toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 2]

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
RESTRICTED LIST	International Living Future Institute (ILFI)	Living Building Challenge 4.0 - Red List of Materials & Chemicals - Effective February 1, 2025 Red List substances to avoid in Living Building Challenge V4.0 projects

SUBSTANCE NOTES: Epoxy resin forms the primary binding matrix of the Base component, providing adhesion to concrete and steel substrates. In the overall product, it reacts with the hardener to create a rigid, crosslinked polymer network responsible for mechanical strength, chemical resistance, and long-term durability.

QUARTZ

ID: 14808-60-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-03-17 10:19:33		
%: 15.0000 - 50.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Filler	

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen**
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route**
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)**
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man**
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources**
CAN	IARC	Group 1 - Agent is Carcinogenic to humans**
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen**
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]**
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]**
CAN	GHS - New Zealand	Carcinogenicity category 1**
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]**
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]**
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1**
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Mineral fillers increase bulk and control the rheological behaviour of the Base. In the overall product, they enhance compressive strength, dimensional stability, and load distribution.

**Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.

FUMED SILICA, CRYSTALLINE-FREE, NANO, LACKING HYDROPHOBIC SURFACE TREATMENT

ID: 112945-52-5

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-03-17 10:19:33		
%: 0.0000 - 10.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Filler	

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists
SUBSTANCE NOTES: Fumed silica is used as a fine filler to adjust viscosity and improve handling stability of the Base. In the cured grout, it supports uniform consistency and resistance to flow under load or gravity.		

ALKYL (C12, C14) GLYCIDYL ETHER

ID: 68609-97-2

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-03-17 10:19:33	
%: 0.0000 - 5.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Viscosity modifier
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
MUL	German FEA - Substances Hazardous to Waters		Class 2 - Hazard to Waters	
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1		H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]	
SKI	GHS - New Zealand		Skin irritation category 2	
SKI	GHS - Australia		H315 - Causes skin irritation [Skin corrosion/irritation - Category 2]	
SKI	GHS - Japan		H315 - Causes skin irritation [Skin corrosion / irritation - Category 2]	
SKI	GHS - New Zealand		Skin sensitisation category 1	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
RESTRICTED LIST	Green Science Policy Institute (GSPI)		GSPI - Six Classes Precautionary List	
			Some Solvents	

HARDENER		%: 25.0000 - 40.0000
PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Polymeric Material
RESIDUALS AND IMPURITIES NOTES: CONMIX LTD. worked with the HPDC Approved Preparer to confirm that all residuals and impurities were considered under the preparation of this HPD. This was accomplished by obtaining full formulation disclosure, including residuals and impurities, down to the 100 ppm threshold.		
OTHER MATERIAL NOTES: All substances in this material are below the reportable threshold.		

2-CYCLOHEXENE-1-OCTANOIC ACID, 5(OR 6)-CARBOXY-4-HEXYL-, COMPD. WITH 2-AMINO-2-METHYL-1-PROPANOL

ID: 68128-58-5

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2026-03-17 10:19:34**

%: **30.0000 - 60.0000**

GreenScreen: **NoGS**

RC: **None**

NANO: **No**

SUBSTANCE ROLE: **Curing agent**

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
None found		No warnings found on HPD Priority Hazard Lists
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Cycloaliphatic amines control the curing reaction rate and improve the stability of the epoxy system. In the final product, they contribute to controlled pot life, high mechanical strength, and resistance to chemicals and moisture.

TALC

ID: **14807-96-6**

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2026-03-17 10:19:33**

%: **5.0000 - 40.0000**

GreenScreen: **BM-1**

RC: **None**

NANO: **No**

SUBSTANCE ROLE: **Filler**

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route
CAN	IARC	Group 2a - Agent is probably Carcinogenic to humans
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]
MAM	GHS - Japan	H370 - Causes damage to organs [Specific target organs/systemic toxicity following single exposure - Category 1]
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Extenders are used to adjust viscosity, improve handling characteristics, and control flow behaviour of the hardener component. In the cured grout, they contribute to dimensional stability and consistent load transfer performance.

QUARTZ

ID: **14808-60-7**

HAZARD DATA SOURCE: **Pharos Chemical and Materials Library**

HAZARD SCREENING DATE: **2026-03-17 10:19:34**

%: **0.0000 - 30.0000**

GreenScreen: **BM-1**

RC: **None**

NANO: **No**

SUBSTANCE ROLE: **Filler**

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen**
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route**
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)**
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man**
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources**
CAN	IARC	Group 1 - Agent is Carcinogenic to humans**
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen**
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]**
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]**
CAN	GHS - New Zealand	Carcinogenicity category 1**
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]**
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]**
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1**

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Fillers increase bulk and assist in balancing the rheology of the hardener. In the overall product, they support compressive strength development and reduce shrinkage during curing.

**Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.

POLYETHYLENEPOLYAMINE, DIMER FATTY ACID CONDENSATE		ID: 68410-23-1	
HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2026-03-17 10:19:34	
%: 0.0000 - 28.0000	GreenScreen: BM-1	RC: None	NANO: No
SUBSTANCE ROLE: Binder			

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
SKI	GHS - New Zealand	Skin corrosion category 1C
EYE	GHS - New Zealand	Serious eye damage category 1

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Polyamide resin functions as a polymeric binder within the hardener, improving flexibility and toughness of the cured epoxy network. In the overall system, it enhances adhesion, crack resistance, and long-term durability under mechanical and thermal stress.

TRIETHYLENETETRAMINE

ID: 112-24-3

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-03-17 10:19:35	
%: 0.0000 - 5.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Curing agent

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
SKI	MAK	Sensitizing Substance Sh - Danger of skin sensitization
MUL	German FEA - Substances Hazardous to Waters	Class 2 - Hazard to Waters
SKI	EU - GHS (H-Statements) Annex 6 Table 3-1	H314 - Causes severe skin burns and eye damage [Skin corrosion/irritation - Category 1A or 1B or 1C]
MAM	GHS - Japan	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1
SKI	GHS - New Zealand	Skin corrosion category 1C
EYE	GHS - New Zealand	Serious eye damage category 1
EYE	GHS - Japan	H318 - Causes serious eye damage [Serious eye damage / eye irritation - Category 1]
SKI	GHS - Japan	H314 - Causes severe skin burns and eye damage [Skin corrosion / irritation - Category 1]
SKI	GHS - Australia	H314 - Causes severe skin burns and eye damage [Skin corrosion/irritation - Category 1A or 1B or 1C]
SKI	GHS - New Zealand	Skin sensitisation category 1
AQU	GHS - New Zealand	Hazardous to the aquatic environment - chronic category 2
REP	GHS - New Zealand	Reproductive toxicity category 2
AQU	GHS - Japan	H411 - Toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 2]
MAM	GHS - Japan	H311 - Toxic in contact with skin [Acute Toxicity (dermal) - Category 3]
MAM	GHS - New Zealand	Acute dermal toxicity category 3
MAM	GHS - Australia	H330 - Fatal if inhaled [Acute toxicity (inhalation) - Category 1 or 2]

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Triethylene tetramine acts as a reactive amine curing agent that initiates crosslinking with the epoxy resin. In the overall product, it contributes to early strength development, bond formation, and chemical resistance of the cured grout.

CARBON BLACK		ID: 1333-86-4		
HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2026-03-17 10:19:35		
%: 0.0000 - 1.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Pigment

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen**
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification**
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route**
CAN	IARC	Group 2b - Possibly carcinogenic to humans**
EYE	GHS - New Zealand	Eye irritation category 2**
CAN	GHS - New Zealand	Carcinogenicity category 2**
CAN	GHS - Japan	H351 - Suspected of causing cancer [Carcinogenicity - Category 2]**
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**
PHY	GHS - Japan	H251 - Self-heating;; may catch fire [Self-heating substances and mixtures - Category 1]**
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Pigments provide colour for visual identification and quality control during mixing and application. In the overall system, they help confirm proper blending of the two components.

**Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.

RUTILE TITANIUM DIOXIDE
ID: 1317-80-2

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2026-03-17 10:19:34	
%: 0.0000 - 1.0000	GreenScreen: LT-1	RC: None	NANO: No	SUBSTANCE ROLE: Pigment
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen**		
CAN	IARC	Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources**		
CAN	MAK	Carcinogen Group 3A - Evidence of carcinogenic effects but not sufficient to establish MAK/BAT value**		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: Pigments provide colour for visual identification and quality control during mixing and application. In the overall system, they help confirm proper blending of the two components.

****Form-Specific Hazard:** This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.



Section 3: Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	CDPH Standard Method - Not tested	
COMPLIANCE TYPE: Self-declaration	ISSUE DATE: 2025-11-07	EXPIRY DATE: No expiration
CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: None		
COMPLIANCE DETAILS:		
COMPLIANCE SCOPE:		
APPLICABLE FACILITIES: UAE		
COMPLIANCE URL:		
COMPLIANCE NOTES:		
MANAGEMENT	ISO 9001:2015 Quality management systems	

COMPLIANCE TYPE: Third-party certification		ISSUE DATE: 2025-10-02	EXPIRY DATE: 2028-10-01
CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: Bureau Veritas			
COMPLIANCE DETAILS:			
COMPLIANCE SCOPE:			
APPLICABLE FACILITIES: 1) Head Office: City Gate Tower, Al Tawuun Area, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006558-001. 2) Warehouse Factory No. 4, Jurf Industrial Zone 3, P.O. Box 88, Ajman, United Arab Emirates. Certificate Number: DU006558-002. 3) Al Quoz, P.O. Box 71285, Dubai, United Arab Emirates. Certificate Number: DU006558-003. 4) Dubai Investment Park 1, P.O. Box 71285, Dubai, United Arab Emirates. Certificate Number: DU006558-004. 5) Industrial Area 12, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006558-005. 6) Dubai Industrial City, P.O. Box 5936, Dubai, United Arab Emirates. Certificate Number: DU006558-006. 7) Zone R, Al Ghail Industrial Zone, NFZ, P.O. Box 88, Ras Al Khaimah, United Arab Emirates. Certificate Number: DU006558-007. 8) Industrial Area 07, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006558-008			
COMPLIANCE URL: https://conmix.com/quality-management			
COMPLIANCE NOTES: 1) Head Office (Sharjah): (a) Design, manufacturing, and supply of Ready Mix Concrete. (b) Manufacturing of Dry Mix Concrete and Mortars. (c) Manufacturing of Cement prepared additives. (d) Manufacturing of construction plaster products. (e) Manufacturing of construction chemicals, Pre Mix Plaster and Paints. (f) Manufacturing of Fire Resistant and Retardant materials. (g) Manufacturing of Wall Coating Materials and Paints. (h) Manufacturing of Glues and prepared adhesives. (i) Coating and treatment of metals. 2) Ajman: (a) Design, manufacturing, and supply of Ready Mix Concrete Coating and Treatment of Metals. 3) Al Quoz: (a) Design, manufacturing, and supply of Ready Mix Concrete. 4) DIP: (a) Design, manufacturing, and supply of Ready Mix Concrete. 5) Industrial Area 12, Sharjah: (a) Design, manufacturing, and supply of Ready Mix Concrete. 6) DIC: (a) Manufacturing of Fire Resistant & Retardant materials. (b) Manufacturing of Construction chemicals, Pre Mix Plaster & Paints. (c) Manufacturing of Wall Coating materials and Paints. 7) Ras Al Khaimah: (a) Manufacturing of Dry Mix Concrete and Mortars. (b) Manufacturing of Construction Plaster Products. (c) Manufacturing of Cement prepared additives. (d) Manufacturing of Glues and prepared adhesives. 8) Industrial Area 07, Sharjah: (a) Manufacturing of construction chemicals.			
MANAGEMENT		ISO 14001:2015 - Environmental management systems	

COMPLIANCE TYPE: Third-party certification		ISSUE DATE: 2025-10-02	EXPIRY DATE: 2028-10-01
CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: Bureau Veritas			
COMPLIANCE DETAILS:			
COMPLIANCE SCOPE:			
APPLICABLE FACILITIES: 1) Head Office: City Gate Tower, Al Tawuun Area, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006556-001. 2) Warehouse Factory No. 4, Jurf Industrial Zone 3, P.O. Box 88, Ajman, United Arab Emirates. Certificate Number: DU006556-002. 3) Al Quoz, P.O. Box 71285, Dubai, United Arab Emirates. Certificate Number: DU006556-003. 4) Dubai Investment Park 1, P.O. Box 71285, Dubai, United Arab Emirates. Certificate Number: DU006556-004. 5) Industrial Area 12, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006556-005. 6) Dubai Industrial City, P.O. Box 5936, Dubai, United Arab Emirates. Certificate Number: DU006556-006. 7) Zone R, Al Ghail Industrial Zone, NFZ, P.O. Box 88, Ras Al Khaimah, United Arab Emirates. Certificate Number: DU006556-007. 8) Industrial Area 07, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006556-008.			
COMPLIANCE URL: https://conmix.com/quality-management			
COMPLIANCE NOTES: 1) Head Office (Sharjah): (a) Design, manufacturing, and supply of Ready Mix Concrete. (b) Manufacturing of Dry Mix Concrete and Mortars. (c) Manufacturing of Cement prepared additives. (d) Manufacturing of construction plaster products. (e) Manufacturing of construction chemicals, Pre Mix Plaster and Paints. (f) Manufacturing of Fire Resistant and Retardant materials. (g) Manufacturing of Wall Coating Materials and Paints. (h) Manufacturing of Glues and prepared adhesives. (i) Coating and treatment of metals. 2) Ajman: (a) Design, manufacturing, and supply of Ready Mix Concrete Coating and Treatment of Metals. 3) Al Quoz: (a) Design, manufacturing, and supply of Ready Mix Concrete. 4) DIP: (a) Design, manufacturing, and supply of Ready Mix Concrete. 5) Industrial Area 12, Sharjah: (a) Design, manufacturing, and supply of Ready Mix Concrete. 6) DIC: (a) Manufacturing of Fire Resistant & Retardant materials. (b) Manufacturing of Construction chemicals, Pre Mix Plaster & Paints. (c) Manufacturing of Wall Coating materials and Paints. 7) Ras Al Khaimah: (a) Manufacturing of Dry Mix Concrete and Mortars. (b) Manufacturing of Construction Plaster Products. (c) Manufacturing of Cement prepared additives. (d) Manufacturing of Glues and prepared adhesives. 8) Industrial Area 07, Sharjah: (a) Manufacturing of construction chemicals.			
MANAGEMENT		ISO 45001:2018 Occupational health and safety management systems	

CERTIFIER/VERIFIER/TESTING LAB/AUDITOR: Bureau Veritas

COMPLIANCE DETAILS:
COMPLIANCE SCOPE:

APPLICABLE FACILITIES: 1) Head Office: City Gate Tower, Al Tawuun Area, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006557-001. 2) Warehouse Factory No. 4, Jurf Industrial Zone 3, P.O. Box 88, Ajman, United Arab Emirates. Certificate Number: DU006557-002. 3) Al Quoz, P.O. Box 71285, Dubai, United Arab Emirates. Certificate Number: DU006557-003. 4) Dubai Investment Park 1, P.O. Box 71285, Dubai, United Arab Emirates. Certificate Number: DU006557-004. 5) Industrial Area 12, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006557-005. 6) Dubai Industrial City, P.O. Box 5936, Dubai, United Arab Emirates. Certificate Number: DU006557-006. 7) Zone R, Al Ghail Industrial Zone, NFZ, P.O. Box 88, Ras Al Khaimah, United Arab Emirates. Certificate Number: DU006557-007. 8) Industrial Area 07, P.O. Box 5936, Sharjah, United Arab Emirates. Certificate Number: DU006557-008.

COMPLIANCE URL: <https://conmix.com/quality-management>

COMPLIANCE NOTES: 1) Head Office (Sharjah): (a) Design, manufacturing, and supply of Ready Mix Concrete. (b) Manufacturing of Dry Mix Concrete and Mortars. (c) Manufacturing of Cement prepared additives. (d) Manufacturing of construction plaster products. (e) Manufacturing of construction chemicals, Pre Mix Plaster and Paints. (f) Manufacturing of Fire Resistant and Retardant materials. (g) Manufacturing of Wall Coating Materials and Paints. (h) Manufacturing of Glues and prepared adhesives. (i) Coating and treatment of metals. 2) Ajman: (a) Design, manufacturing, and supply of Ready Mix Concrete Coating and Treatment of Metals. 3) Al Quoz: (a) Design, manufacturing, and supply of Ready Mix Concrete. 4) DIP: (a) Design, manufacturing, and supply of Ready Mix Concrete. 5) Industrial Area 12, Sharjah: (a) Design, manufacturing, and supply of Ready Mix Concrete. 6) DIC: (a) Manufacturing of Fire Resistant & Retardant materials. (b) Manufacturing of Construction chemicals, Pre Mix Plaster & Paints. (c) Manufacturing of Wall Coating materials and Paints. 7) Ras Al Khaimah: (a) Manufacturing of Dry Mix Concrete and Mortars. (b) Manufacturing of Construction Plaster Products. (c) Manufacturing of Cement prepared additives. (d) Manufacturing of Glues and prepared adhesives. 8) Industrial Area 07, Sharjah: (a) Manufacturing of construction chemicals.

+ Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

E Section 5: General Notes

NanoGrout SG is a high-performance, two-component, epoxy-based structural adhesive and anchor grout designed for anchoring, bonding, and precision structural fixing applications. Supplied in paste and pourable grades, the system is mixed on site to form a dense, cohesive grout with excellent adhesion

and gap-filling capability, ensuring strong bonding to concrete and steel substrates. The formulation combines epoxy resin with amine and polyamide hardeners, mineral fillers, and performance additives to provide controlled rheology, low water absorption, and high chemical resistance without reliance on water.

The grout is engineered for demanding civil, infrastructure, and industrial environments where high mechanical strength, durability, and bond reliability are critical. NanoGrout SG develops high early and long-term strength, exhibits non-sag behaviour on vertical and overhead applications, and maintains performance under static and dynamic loading conditions. Typical applications include anchor bolts, starter bars, base plate bolt pockets, bridge bearings, segmental precast bonding, and structural strengthening works, offering a reliable solution for long-term structural anchoring and bonding requirements.

MANUFACTURER INFORMATION

MANUFACTURER: **CONMIX LTD**
ADDRESS: **9th Floor, The City Gate Tower Opposite Ansar Mall**
Al Khalidiya District, Sharjah 5936
COUNTRY: **United Arab Emirates**

WEBSITE: **www.conmix.com**
CONTACT NAME: **Alfred Bulaya**
TITLE: **QC Engineer**
PHONE: **+971 6 5126325**
EMAIL: **conmix@conmix.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold	Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold	Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold	Substances listed individually per threshold indicated per product

Nano	Composed of nano scale particles or nanotechnology
Third Party Verified	Verification by independent certifier approved by HPDC
Preparer	Third party preparer, if not self-prepared by manufacturer
Applicable facilities	Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.