

Name

BASWAphon Frosted

Product ID

Website

www.baswa.com

Classification

Manufacturer

BASWA acoustic

Address

Marmorweg 10
Baldegg 6283
Switzerland

Contact Name

Bernhard Hanisch

Title

operations manager

Phone

+41419140211

Email

bernhard.hanisch@baswa.com

Health Product
DECLARATION

1.0

Description

BASWAphon is the original, most specified sound absorbing plaster system, with over 25 years of installations. Up to 5,000 square feet without a control joint can be applied to flat, curved, domed, or vaulted surfaces in any color. NRCs up to 1.05 make it the most sound absorptive plaster on the market.

Finishes are mold, moisture and mildew resistant. Perfect for spas, natatoriums or porte-cochères. BASWAphon coatings are made of a durable crushed marble aggregate. No panel sanding necessary; no telegraphing seams.

Up to 95% recycled materials, SDS friendly, high light reflectance and a high R-value; California Section 01350 compliant. Swiss engineered, US made components.

Release Date

2015-08-18

Expiry Date

2018-08-18

HPD URL

<https://builder.hpd-collaborative.org/uploads/files/hpds/942/3305-20150818093904.pdf>

☒ Self-declared

☐ Second Party

☐ Third Party

Certifier

Certificate #

SUMMARY DISCLOSURE

The content of this product was assessed for health hazard warnings as required using Pharos

Residuals Disclosure

☐ Measured 100 ppm (ideal)
☐ Measured 1000 ppm
☐ Predicted by process chemistry
☒ As per MSDS (1,000 & 10,000 ppm)
☐ Not disclosed
☐ Other

Full Disclosure of Intentional Ingredients

☒ Yes ☐ No

Full Disclosure of Known Hazards

☒ Yes ☐ No

Disclosure Notes

Contents in Descending Order of Quantity

Marble , Glass / Mineral Fiber (post-consumer recycled) , Glasswool , ACRYLATES , Aluminium hydroxide oxide , Rutile titanium dioxide , ACETIC ACID, GLACIAL , 5-Methylfurfural , TRIETHYLENE GLYCOL MONOBUTYL ETHER , nonyl 2-pentyl ester sulfurous acid

Hazards

☐ PBT (Persistent Bioaccumulative Toxic)
☒ Cancer
☐ Gene Mutation

☐ Development
☐ Reproductive
☐ Endocrine
☒ Respiratory

Highest concern GreenScreen score - List Translator Unspecified

☐ Neurotoxicity
☐ Mammal
☒ Skin or Eye
☐ Aquatic toxicity

☐ Land toxicity
☐ Physical hazard
☐ Global warming
☐ Ozone depletion

☐ Multiple
☒ Unknown

Total VOC Content

Material (g/L)

Regulatory (g/L)

1.00

Does the product contain exempt VOCs?

Are there VOC-free tints available?

☐ N/A ☐ Yes ☒ No

☐ N/A ☒ Yes ☐ No

Notes
Pintasol

Certifications + Compliance

VOC Emissions

CA Section 01350 (CHPS) Emission Test - CDPH/EHLB Standard Method V1.1 -

VOC Content

Not tested

Health Product Declaration v1.0 - hpdcollaborative.org - Page 1 of 5

The HPD Standard is solely a declaration of product content and direct health hazards associated with exposure to its individual contents. It is not a full assessment of environmental impacts from the life cycle of this product. It is not an assessment of risks associated with actual use of the product. It does not address the potential health impacts of substances used or created during manufacture that do not appear in the final product as residuals, nor substances created during combustion or other degradation processes.

This Health Product Declaration was generated following the requirements of the noted Standard version and is valid for a total of three years after date of issue or three months after a substantive change of product contents occurs. Users should verify that this Health Product Declaration is compliant with the most current version of the HPD Standard. Accuracy of claims made in this Health Product Declaration is the sole responsibility of the listed manufacturer and certifier (if applicable). The HPD Collaborative does not warrant any claim made herein, explicit or implicit. The HPD Standard is an “open standard” developed and managed by the HPD Collaborative, a nonprofit organization. For more information, visit hpdcollaborative.org.

CONTENT IN DESCENDING ORDER OF QUANTITY

All ingredients must be assessed for health warnings against Priority Hazard Lists, regardless of disclosure level. Priority Hazard Lists and information on the GreenScreen Benchmarks can be found at www.hpdcollaborative.org/hazardlists.
GS: GreenScreen Benchmark; **RC:** Recycled Content, **PC:** Post Consumer, **PI:** Post Industrial (Pre-consumer), **BO:** Both; **Nano:** comprised of nanoscale particles or nanotechnology

Name	CAS RN	% weight	GS	RC	Nano	Role
Hazard A	Warning A					
Hazard B	Warning B					
Hazard C	Warning C					
Hazard D	Warning D					
Hazard E	Warning E					
Notes						
Marble	Not registered	27 - 32 %	LT-U	PI	N	gravel
None found	No warnings found on HPD Priority lists					
Glass / Mineral Fiber (post-consumer recycled)		23 - 30 %		U	N	sound absorption layer
None found	No warnings found on HPD Priority lists					
Glasswool	Not registered	15 - 33 %		U	N	sound absorption layer
None found	No warnings found on HPD Priority lists					
ACRYLATES		1 - 2 %		U	N	acrylate binder
None found	No warnings found on HPD Priority lists					
Aluminium hydroxide oxide	24623-77-6	1 - 2 %	LT-U	U	N	flame retardant
None found	No warnings found on HPD Priority lists					
Rutile titanium dioxide	1317-80-2	1 %	LT-U	U	N	color pigment

CANCER	NIOSH-C: Occupational carcinogen (also in Prop 65, IARC, MAK)					
ACETIC ACID, GLACIAL	64-19-7	R	2			Contaminant
RESPIRATORY	AOEC: Asthmagen (ARrs) - sensitizer-induced & irritant-induced					
SKIN IRRITATION	EU H-Statements: H314 Causes severe skin burns and eye damage (also in EU R-Phrases)					
5-Methylfurfural	620-02-0	R				Contaminant
None found	No warnings found on HPD Priority lists					
TRIETHYLENE GLYCOL MONOBUTYL ETHER	143-22-6	R	LT-U			Contaminant
EYE IRRITATION	EU H-Statements: H318 Causes serious eye damage (also in EU R-Phrases)					
nonyl 2-pentyl ester sulfurous acid	1000309-15-8	R				Unknown
None found	No warnings found on HPD Priority lists					

CERTIFICATIONS AND COMPLIANCE

Certifying Party = First: Manufacturer's self-declaration; Second: Verification by trade association or other interested party; Third: Verification by independent certifier (ideal).
Applicable facilities = Manufacturing sites to which testing applies.

Type	Standard or Certification			Certifier or Laboratory
	Certifying Party	Issue Date	Expiry Date	Certificate URL
	Applicable Facilities			
	Notes			
VOC Emissions	CA Section 01350 (CHPS) Emission Test - CDPH/EHLB Standard Method V1.1 - Classroom & Office scenario			Berkeley Analytical
	1st party manufacturer claim	2012-06-21		https://builder.hpd-collaborative.org/uploads/files/certifications/942/1426253364.pdf
	ALL			
	Potential Applications ☐ ANSI/ASHRAE/USGBC/IES Standard 189.1-2009, 8.4.2.6: Ceiling & Wall Systems ☐ USGBC LEED for Healthcare, 2009 (Feb 2011), IEQ Credit 4: LEM, Group 2 - Wall & Ceiling Finishes ☐ USGBC LEED for Schools, 2009, IEQ Credit 4.6: LEM - Ceiling & Wall Systems ☐ Collaborative for High Performance Schools (CHPS) rating system, 2009 Criteria EQ2.2.6: Ceiling & Wall Systems ☐ Green Guide for Healthcare, V2.2, 2007, EQ Credit 4.2: LEM - Wall & Ceiling Finishes ☐ ANSI/GBI 01-2010 Green Building Assessment Protocol, 2010, Table 12.2.1-B: Walls			
VOC Content	Not tested			

Recycled Content	Not tested			
		2011-10-21		www.eurofins.com
	Baldegg, Switzerland Gotha, Germany Chardon, Ohio			

ACCESSORY MATERIALS

This section is for additional products required by warranty or recommended by the manufacturer for installation (such as adhesives, fasteners, or factory coatings) or for maintenance, cleaning, or operations. Refer to Health Product Declarations, published separately, for a complete view of these products.
Note: This declaration is not intended to address hazards of the installation process.

Required or Recommended Product	URL for Companion Health Product Declaration
Condition when required or recommended and/or other notes	

NOTES

The BASWAphon Frosted Finish, a BASWA acoustic System, is for wall and ceiling applications in spaces where sound absorption is needed in a wide range of frequencies but keeping the original design aesthetic is important. BASWAphon Supporting Panels, BASWAphon Fill, and sprayed BASWAphon Base comprises the BASWAphon Frosted Finish. Individual System components cannot be used alone; ithe BASWAphon System's hig performancce and monolithic appearance through the amalgamation of the components.