

CLASSIFICATION: 07 84 00 Firestopping, 07 84 13 Penetration Firestopping

PRODUCT DESCRIPTION: SpecSeal® Closet Flange Firestop Gaskets are one-piece, molded rubber, intumescent pads that install beneath a 3 or 4” (76 or 102 mm) closet flange to effectively firestop the opening. The die cut rubber gasket is perforated to delineate removable inserts sized to accommodate various outer diameters of toilet flanges. Traditional firestopping methods require the firestop material to be applied around the pipe prior to setting the toilet flange, which can be problematic if the firestop material is not recessed a sufficient distance from the top to accommodate the throat of the flange. The alternative is to apply the firestopping from the underside of the floor, necessitating the use of ladders or lifts. SpecSeal® Closet Flange Firestop Gaskets solve the problem by providing a laborfriendly method of properly firestopping the opening. Applications SpecSeal® Closet Flange Firestop Gaskets are designed to allow the drain pipe connected to a toilet flange to be properly firestopped without the need for firestop caulk for typical floor assemblies with plastic or metal pipes.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

☐ Nested Materials Method

☒ Basic Method

Threshold Disclosed Per

☐ Material

☒ Product

Threshold level

☐ 100 ppm

☒ 1,000 ppm

☐ Per GHS SDS

☐ Per OSHA MSDS

☐ Other

Residuals/Impurities

☒ Considered

☐ Partially Considered

☐ Not Considered

Explanation(s) provided for Residuals/Impurities?

☒ Yes

☐ No

All Substances Above the Threshold Indicated Are:

Characterized

☐ Yes Ex/SC

☒ Yes

☐ No

% weight and role provided for all substances.

Screened

☐ Yes Ex/SC

☒ Yes

☐ No

All substances screened using Priority Hazard Lists with results disclosed.

Identified

☐ Yes Ex/SC

☐ Yes

☒ No

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SPECSEAL® CLOSET FLANGE FIRESTOP GASKET [GRAPHITE LT-UNK UNDISCLOSED LT-UNK UNDISCLOSED NoGS METHYLENE BISPHENYL DIISOCYANATE (PURE MDI) LT-UNK | RES | MUL | SKI | EYE | CAN 2,2'-BIS-6-TERC.BUTYL-P-KRESYLMETHAN LT-P1 | END | REP UNDISCLOSED LT-UNK | RES | MUL | CAN]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

None.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: N/A

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients, Option 1

Third Party Verified?

☐ Yes

☒ No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2019-03-22

PUBLISHED DATE: 2019-03-22

EXPIRY DATE: 2022-03-22

SpecSeal Closet Flange Firestop Gasket
hpdrepository.hpd-collaborative.org

HPD v2.1.1 created via HPDC Builder Page 1 of 5

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- *Basic Inventory method with Product-level threshold.*
- *Nested Material Inventory method with Product-level threshold*
- *Nested Material Inventory method with individual Material-level thresholds*

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.1, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-1-standard

SPECSEAL® CLOSET FLANGE FIRESTOP GASKET

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: This material does not contain any residuals.

OTHER PRODUCT NOTES: This material does not contain any residuals.

GRAPHITE

ID: 7782-42-5

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-03-22

%: 30.0000 - 60.0000

GS: LT-UNK

RC: None

NANO: No

ROLE: Intumescent

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

No hazards found

SUBSTANCE NOTES: This material is the intumescent in the product.

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-03-22

%: 20.0000 - 45.0000

GS: LT-UNK

RC: None

NANO: No

ROLE: Binder

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

No hazards found

SUBSTANCE NOTES: This material is part of the binder in the product.

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-03-22

%: 15.0000 - 40.0000

GS: NoGS

RC: None

NANO: No

ROLE: plasticizer

HAZARD TYPE

AGENCY AND LIST TITLES

WARNINGS

No hazards found

SUBSTANCE NOTES: This material is the plasticizer in the product.

METHYLENE BISPHENYL DIISOCYANATE (PURE MDI)

ID: 101-68-8

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2019-03-22

%: 1.0000 - 4.0000

GS: LT-UNK

RC: None

NANO: No

ROLE: Binder

HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS
RESPIRATORY	AOEC - Asthmagens	Asthmagen (G) - generally accepted
RESTRICTED LIST	US EPA - PPT Chemical Action Plans	EPA Chemical of Concern - Action Plan published
SKIN IRRITATION	EU - GHS (H-Statements)	H315 - Causes skin irritation
SKIN SENSITIZE	EU - GHS (H-Statements)	H317 - May cause an allergic skin reaction
EYE IRRITATION	EU - GHS (H-Statements)	H319 - Causes serious eye irritation
RESPIRATORY	EU - GHS (H-Statements)	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
CANCER	EU - GHS (H-Statements)	H351 - Suspected of causing cancer
RESPIRATORY	US EPA - PPT Chemical Action Plans	Inhalation sensitizer causing asthma and lung damage
CANCER	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels
RESPIRATORY	MAK	Sensitizing Substance Sah - Danger of airway & skin sensitization
SUBSTANCE NOTES: This material is part of the binder in the product.		

2,2'-BIS-6-TERC.BUTYL-P-KRESYLMETHAN

ID: 119-47-1

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-03-22		
%: 0.2000 - 1.0000	GS: LT-P1	RC: None	NANO: No	ROLE: antioxidant
HAZARD TYPE	AGENCY AND LIST TITLES		WARNINGS	
ENDOCRINE	TEDX - Potential Endocrine Disruptors		Potential Endocrine Disruptor	
REPRODUCTIVE	Australia - GHS		H360F - May damage fertility	
SUBSTANCE NOTES: This material is the antioxidant in the product.				

UNDISCLOSED

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2019-03-22		
%: 0.2000 - 1.0000	GS: LT-UNK	RC: None	NANO: No	ROLE: Binder
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
RESPIRATORY	AOEC - Asthmagens	Asthmagen (G) - generally accepted		
RESTRICTED LIST	US EPA - PPT Chemical Action Plans	EPA Chemical of Concern - Action Plan published		
RESPIRATORY	US EPA - PPT Chemical Action Plans	Inhalation sensitizer causing asthma and lung damage		
CANCER	MAK	Carcinogen Group 4 - Non-genotoxic carcinogen with low risk under MAK/BAT levels		
RESPIRATORY	MAK	Sensitizing Substance Sah - Danger of airway & skin sensitization		
SUBSTANCE NOTES: This material is part of the binder in the product.				

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS		N/A		
CERTIFYING PARTY:	Self-declared	ISSUE	EXPIRY	CERTIFIER
APPLICABLE FACILITIES:	All.	DATE:	DATE:	OR LAB:
CERTIFICATE URL:	https://files.stifirestop.com/5.%20Safety%20Data%20Sheets/1.%20English/SDS_Closet%20Flange%20Firestop%20Gasket.pdf	2017-01-30		Self-declared.
CERTIFICATION AND COMPLIANCE NOTES: Not Applicable. See SDS (Certificate URL).				

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Specifications: The firestop system for the toilet flange shall be a molded, one-piece intumescent gasket with removable inserts to accommodate various outer diameters of toilet flanges classified by Underwriters Laboratories Inc. (UL) as a fill, void, or cavity material when tested to ASTM E814 (ANSI/UL1479) or CAN/ULC-S115 for up to a 2 hr rating. **Specified Divisions:** Division 7 07 84 13 Penetration Firestopping Division 23 23 00 00 HVAC **Performance:** SpecSeal® Closet Flange Firestop Gaskets have been successfully tested in accordance with ASTM E814 (ANSI/UL1479) and CAN/ULC-S115 in one and two hour fire-rated floor assemblies. Consult factory for individual system designs and application requirements.

MANUFACTURER INFORMATION

MANUFACTURER: **Specified Technologies Inc.**

ADDRESS: **210 Evans Way
Somerville NJ 08876, United States**

WEBSITE: **www.stifirestop.com**

CONTACT NAME: **George Gornick, LEED Green**

Associate

TITLE: **Applications Engineer**

PHONE: **800-992-1180, Ext. 1013**

EMAIL: **ggornick@stifirestop.com**

KEY

OSHA MSDS Occupational Safety and Health Administration Material Safety Data Sheet

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

MAM Mammalian/systemic/organ toxicity

MUL Multiple hazards

NEU Neurotoxicity

OZO Ozone depletion

PBT Persistent Bioaccumulative Toxic

PHY Physical Hazard (reactive)

REP Reproductive toxicity

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

LAN Land Toxicity

NF Not found on Priority Hazard Lists

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (insufficient data to benchmark)

LT-P1 List Translator Possible Benchmark 1

LT-1 List Translator Likely Benchmark 1

LT-UNK List Translator Benchmark Unknown (insufficient information from List Translator lists to benchmark)

NoGS Unknown (no data on List Translator Lists)

Recycled Types

PreC Preconsumer (Post-Industrial)

PostC Postconsumer

Both Both Preconsumer and Postconsumer

Unk Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material

Nested Method / Product Threshold Substances listed within each material per threshold indicated per product

Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.